



○ = Corner

T. 144 R. 31 M. 5TH Coordinates: X NE 16 Y 9, 10, 15, 16  
 Corner common to sections

EXISTING SURVEYS

Original Government Survey				
Year surveyed <u>1875</u>				
Original monument <u>Post</u>				
Bearing Trees				
Species	<u>w. pine</u>	<u>wilme</u>	<u>wilme</u>	<u>R. oak</u>
Diameter	<u>30"</u>	<u>30"</u>	<u>28"</u>	<u>12"</u>
Bearing	<u>W Pst</u>	<u>S43 1/2 E</u>	<u>N73 E</u>	<u>N22 W</u>
Distance	<u>50 LKS</u>	<u>85 LKS</u>	<u>98 LKS</u>	<u>57 LKS</u>

Original Evidence Found	
Year of search	By
Monument found	
Original Bearing Trees Found	
Species	
Diameter	
Bearing	
Distance	

Subsequent Corner Restoration	
Year surveyed	<u>1913</u> By <u>John Curo</u>
Location filed <u>COUNTY SURVEY RECORD BOOK 'A' Pgs 5-611</u>	
Monument <u>END OLD GOVT R.T. STUMPS: 30" W. PINE</u> <u>S43-30E 85 LKS, 28" W. PINE N73E 98 LKS SET</u> <u>2 1/2 x 48" GALV. I.P. W/ CAR</u>	

Evidence of Subsequent Corner Restoration	
Year of search	<u>1930</u> By <u>GLO</u>
<u>End 1/2" Cass Co. I.P. w/galv. Cap and Stumps</u> <u>o P NE &amp; SE BITS iron at intersection 9/10</u> <u>o F roads N-S-E-W. Fence caps bear: 76/15</u> <u>N46 1/2 E 72 LKS, S47 3/4 E 72 LKS,</u> <u>S38 3/4 W 61 LKS, N47 W 72 LKS.</u>	

Bearing Trees, Reference Objects	
Species	<u>PINE</u> <u>OAK</u>
Diameter	<u>STUMP</u> <u>6"</u>
Bearing	<u>S57-47W</u> <u>N35 W</u>
Distance	<u>80.50'</u> <u>31.50'</u>

Bearing Trees, Reference Objects			
<u>OAK</u>	<u>Poplar</u>	<u>Pine</u>	<u>Poplar</u>
<u>10"</u>	<u>14"</u>	<u>14"</u>	<u>5"</u>
<u>N48-26E</u>	<u>S7 1/2 E</u>	<u>S48-20W</u>	<u>N48 1/2 W</u>
<u>47 LKS</u>	<u>406 LKS</u>	<u>398 LKS</u>	<u>107 LKS</u>

J-13 T. 144 R. 31

Subsequent Corner Restoration	
Year surveyed	<u>1979</u> By <u>HWY DEPT</u>
Location filed	
Monument <u>FD 2" CAPED IRON PIPE</u> <u>POWER POLE SE 51.7'</u> <u>8" OAK NW 107.4'</u>	

Evidence of Subsequent Corner Restoration Found	
Year of search	By