


Index No. P9

CASS COUNTY LAND CORNER RECORD

T. 144 R. 31 M. 5TH Coordinates: X _____ Y _____
E114 20 Corner common to sections 20, 21



EXISTING SURVEYS

Original Government Survey
 Year surveyed 1875
 Original monument Post

Bearing Trees

Species	<u>Tan</u>	<u>WILNE</u>		
Diameter	<u>6"</u>	<u>18"</u>		
Bearing	<u>N17W</u>	<u>S86W</u>		
Distance	<u>37 LKS</u>	<u>48 LKS</u>		

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration
 Year surveyed 1922 By E.R. HORST
 Location filed COUNTY BOOK "D" P. 64
 Monument END S.W. WILNE U.S. B.T.

Evidence of Subsequent Corner Restoration
 Year of search 1931 By GLO
Find stump of S.W. B.T. set 2436" I.P. w/brass cap
114
S20/S21
1931

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

<u>SPRUCE</u>	<u>WILNE</u>	<u>Fence corner</u>
<u>8"</u>	<u>8"</u>	<u>N 1/2 E</u>
<u>N31 3/4 E</u>	<u>N78W</u>	<u>N81 1/4 W</u>
<u>48 LKS</u>	<u>108 LKS</u>	<u>40 LKS</u>

Subsequent Corner Restoration
 Year surveyed 1970 By C. H. Hart Dept
 Location filed in SQUAW POINT RD file
 Monument BRASS cap
TIES: Aspen 4" SW 76.0'
W. oak 8" SE 71.0'

1925 Minn Hart Dept - Plu map in Recorder's office
walker to Cass Lake
1 1/2" I.P. w/ brass cap 1717.3' E. of G

Evidence of Subsequent Corner Restoration Found
 Year of search _____ By _____