Index No. R 25

CASS COUNTY LAND CORNER RECORD

T. 145 R. 28 M. 5TH Coordinates: X _____ Y _____

NE 25 Corner common to sections 24, 25 AND 19, 30 - 145 - 27



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument Post

Bearing Trees

Species	Tam	Tqm	Tqm	Tqm
Diameter	6"	6"	6"	4"
Bearing	N52W	N24E	S60W	S39E
Distance	10 Lks	16 Lks	12 Lks	29 Lks

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1912 By JOHN CURD

Location filed COUNTY SURVEY RECORD BOOK "A" P. 544-550

Monument FND OLD GOVT STAKE & B.T.S: 6" TAM N24E 16 LKS, 6" TAM N52W 10 LKS, 4" TAM S39E 29 LKS. 6" TAM S60W 12 LKS. SET 2½"x48" GALV. I.P. W/ 3" CAP

Bearing Trees, Reference Objects

Species	TAM.	TAM	TAM	TAM.
Diameter	3"	3"	3"	4"
Bearing	S53-3/4E	S61-35W	N28-18W	N32-50E
Distance	12.54'	16.44'	9.56'	26.49'

Evidence of Subsequent Corner Restoration

Year of search OCT 20, 1926 By R.A. DAHMS, ENGR

FOUND CAST IRON MONUMENT

TRANSIT NOTES CASS S.A.R. #9

BOOK 156, PAGE 9

792' S. OF STA. 68+58

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____