


Index No. A 21

CASS COUNTY LAND CORNER RECORD

T. 145 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 2 Corner common to sections 1, 2 AND 35, 36-146-30



EXISTING SURVEYS

**Original Government Survey**

Year surveyed 1873  
Original monument lost

Species	Bearing	Trees	Distance
<u>N. Pine</u>	<u>N 10"</u>	<u>N. Pine</u>	<u>24"</u>
<u>20"</u>	<u>10"</u>	<u>10"</u>	<u>24"</u>
<u>N 64 E</u>	<u>N 47 W</u>	<u>56 W</u>	<u>529 E</u>
<u>74 US</u>	<u>9 LKs</u>	<u>93 US</u>	<u>90 US</u>

**Original Evidence Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

**Original Bearing Trees Found**

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

**Subsequent Corner Restoration**

Year surveyed 1933 By GLO  
Location filed Sec. of State  
Monument Set concrete man 24" long 6" dia w/ brass cap  
T146 N R30W  
S35/S36  
S2/S1

**Bearing Trees, Reference Objects**

Species	Diameter	Bearing	Distance
<u>J. Pine</u>	<u>7"</u>	<u>N 80-07 E</u>	<u>227 US</u>
<u>J. Pine</u>	<u>8"</u>	<u>S 6 1/2 E</u>	<u>71 LKs</u>
<u>Poplar</u>	<u>4"</u>	<u>S 31 1/2 W</u>	<u>42 US</u>
<u>J. Pine</u>	<u>7"</u>	<u>N 33 1/4 W</u>	<u>333 US</u>

**Evidence of Subsequent Corner Restoration**

Year of search 1962 By PETE MEYER  
Found GLO monument in good condition.

**Bearing Trees, Reference Objects**

Species	Diameter	Bearing	Distance
<u>Red Pine</u>	<u>7"</u>	<u>S 17 W</u>	<u>70.5'</u>
<u>Red Pine</u>	<u>7"</u>	<u>S 62 E</u>	<u>37.3'</u>
<u>Red Pine</u>	<u>8"</u>	<u>N 67 E</u>	<u>50.6'</u>

**Subsequent Corner Restoration**

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

**Evidence of Subsequent Corner Restoration Found**

Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - PETE MEYER - 1962