


Index No. R 9

CASS COUNTY LAND CORNER RECORD

T. 145 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 29 Corner common to sections 20, 21, 28, 29



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Species	Bearing	Trees	
<u>Bl. oak</u>	<u>Sugar</u>	<u>W. Pine</u>	<u>Elm</u>
<u>8"</u>	<u>8"</u>	<u>24"</u>	<u>8"</u>
<u>N45W</u>	<u>S76W</u>	<u>N14E</u>	<u>S26E</u>
<u>62 LKS</u>	<u>38 LKS</u>	<u>90 LKS</u>	<u>82 LKS</u>

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

O = Corner

Subsequent Corner Restoration

Year surveyed 1933 By GLO
Location filed SEC. OF STATE
Monument Set concrete mon 24" long 6" dia w/brass cap
T145W R30W
S20/S21
S29/S28

Bearing Trees, Reference Objects 1933

Species	Bearing	Distance
<u>W. Pine</u>	<u>N38 1/4 E</u>	<u>10.7 LKS</u>
<u>W. Ash</u>	<u>S76 1/4 E</u>	<u>4.3 LKS</u>
<u>W. Ash</u>	<u>S19 1/2 W</u>	<u>9.1 LKS</u>
<u>W. Pine</u>	<u>N50 1/2 W</u>	<u>7.3 LKS</u>

Evidence of Subsequent Corner Restoration

Year of search 1982 By Gary Stevenson
Corner Certificate
in 1979 USFS End Brass cap in concrete
and all 4 1933 B.T.S - Ash SE Broken off

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>W. Pine</u>	<u>N55 W</u>	<u>48.30'</u>
<u>W. Pine</u>	<u>N38 E</u>	<u>70.75'</u>
<u>B. Ash</u>	<u>S19 W</u>	<u>60.25'</u>
<u>W. Ash</u>	<u>S63 W</u>	<u>48.63'</u>

~ 1933 B.T.S ~

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Gary Stevenson - by USFS - 1984
Doc. # 279382 dated 1982

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____