


T. 145 R. 30 M. 5th Coordinates: X _____ Y _____

NE 33 Corner common to sections 27, 28, 33, 34



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument Post

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species	Birch	Ironwood	Linden
Diameter	10"	4"	6"
Bearing	N 54° E	S 57° E	S 10° W
Distance	14 links	12 links	13 links

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 7/1933 By W.W. Bandy, Surveyor, GLO
Location filed: MN Historical Society, Notes pg 59 T145N R30
Monument: Set 6" conc. cylinder with brass tablet S 28 | S 27
at proportionate distance, no remaining evidence S 33 | S 34
of original post or witnesses, up 4" and 1933
witnessed as follows.

Evidence of Subsequent Corner Restoration

Year of search 7/1934 By C.J. Mendenhall, CCC
Location filed: USFS Form 874-9
Monument: Brass cap on cement
up 5" and witnesses as follows.
10" Red Oak, S 86°30' W, 32.8 links(21.65') Metal Location
poster.

Bearing Trees, Reference Objects

Species	Red Oak	Balsam	Burr Oak	Burr Oak
Diameter	14"	6"	4"	5"
Bearing	N 63 1/4° E	S 32 1/2° E	S 57 1/4° W	N 11 1/2° W
Distance	48 links	60 links	28 links	21 links

Bearing Trees, Reference Objects

Species	Red Oak	White Pine	White Oak	White Oak
Diameter	14"	6"	3"	4"
Bearing	N 64° E	S 32° E	S 57° W	N 12°30' W
Distance	47.3 links	59.5 links	28 links	21.5 links

Subsequent Corner Restoration

Year surveyed 10/1970 By C.R. Krause, USFS
Location filed: USFS Book 2, page 34
Monument: Found GLO concrete with brass tablet
up 6", in good condition, blue line E-W and witnessed.
19" Red Oak, N 63° E, 31.7'(1933) scribe rotted
Balsam stub, S 32° E, 39.6'(1933) 36" high stub
6" White Oak, S 57° W, 18.5'(1933) FS 54-4 sign
9" White Oak, N 11° W, 13.9'(1933) scribe overgrown
8" Red Oak, N 58° E, 50.7' scribed
9" Twin Red Oak, S 25° E, 26.5' scribed
8" Oak snag, SE, 5' FSLP


Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed: _____
Monument: _____

Index No. V 13

CASS COUNTY LAND CORNER RECORD

T. 145 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 33 Corner common to sections 27, 28, 33, 34



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument bst

Original Evidence Found

Year of search _____ By _____
Monument found _____

	Bearing Trees		
Species	<u>Birch</u>	<u>Ironwood</u>	<u>Lind</u>
Diameter	<u>10"</u>	<u>4"</u>	<u>6"</u>
Bearing	<u>N54E</u>	<u>S57E</u>	<u>S10W</u>
Distance	<u>14LKS</u>	<u>12LKS</u>	<u>13LKS</u>

Original Bearing Trees Found			
Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1933 By GLO
Location filed Sec of State
Monument Set concrete mon. 24" long 6" dia w/ brass cap
T145N R30W
S28 | S27
S33 | S34

Evidence of Subsequent Corner Restoration

Year of search 1970 By William Okerman
Found GLO monument in good condition.

Bearing Trees, Reference Objects 1933

	<u>R. oak</u>	<u>Balsam</u>	<u>Br. oak</u>	<u>Br. oak</u>
Species				
Diameter	<u>14"</u>	<u>6"</u>	<u>4"</u>	<u>5"</u>
Bearing	<u>N63 1/4 E</u>	<u>S30 1/2 E</u>	<u>S57 1/4 W</u>	<u>N11 1/2 W</u>
Distance	<u>48LKS</u>	<u>60LKS</u>	<u>28LKS</u>	<u>21LKS</u>

Bearing Trees, Reference Objects

	<u>B. Oak</u>	<u>Twin R. Oak</u>	<u>W. Oak</u>
Species			
Diameter	<u>8"</u>	<u>9"</u>	<u>6"</u>
Bearing	<u>N58E</u>	<u>S25E</u>	<u>S57W</u>
Distance	<u>50.70'</u>	<u>26.50'</u>	<u>18.50'</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - BILL OKERMAN - 1970

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____