


T. 145 R. 30 M. 5th Coordinates: X _____ Y _____

MC #2 Corner common to sections 36 and 31-145-29



● = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Original Evidence Found

Year of search 1900 by COE
Monument found _____

Lake Winnibigoshish Map

Bearing Trees

Species	<u>Cedar</u>	<u>Cedar</u>
Diameter	<u>5"</u>	<u>5"</u>
Bearing	<u>N 78° E</u>	<u>S 22° W</u>
Distance	<u>22 links</u>	<u>34 links</u>

Original Bearing Trees Found


Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Subsequent Corner Restoration

Year surveyed 1903 By T.M. Fowble, COE
Location filed: Lake Winnibigoshish Reservoirs Map
Monument:
Indicates original corner evidence recovered.

Evidence of Subsequent Corner Restoration

Year of search 6/1933 By W.W. Bandy, Surveyor, GLO
Location filed: MN Historical Society, notes page 2
Monument: Set 1"x 36" Iron Pipe with brass cap at proportionate distance, on S. shore of Sucker Lake and marked new witnesses as follows.



Bearing Trees, Reference Objects

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Bearing Trees, Reference Objects

Species	<u>White Birch</u>	<u>Cedar</u>
Diameter	<u>8"</u>	<u>12"</u>
Bearing	<u>S 45° E</u>	<u>N 51 1/2° W</u>
Distance	<u>30 links</u>	<u>22 links</u>

Subsequent Corner Restoration

Year surveyed 1/1962 By R.H. McDonald, USFS
Location filed: USFS Book 1, page 3
Monument: Found GLO brass cap and witnesses as follows.
10" Birch, S 45° E, 19.8' (1933) scribe overgrown
Cedar Stub, N 52° W, 14.52' (1933) scribe visible
12" Elm, S 25°30' W, 47.2' marked MC BT

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed: _____
Monument: _____

