


T. 145 R. 31 M. 5TH Coordinates: X _____ Y _____
N 4 17 Corner common to sections 8, 17



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875
 Original monument lost

Bearing Trees

Species	<u>J. Pine</u>	<u>J. Pine</u>	_____
Diameter	<u>7"</u>	<u>8"</u>	_____
Bearing	<u>S20W</u>	<u>N42E</u>	_____
Distance	<u>16 LKS</u>	<u>21 LKS</u>	_____

Original Evidence Found

Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1906 By JOHN CURO
 Location filed COUNTY SURVEY RECORD BOOK "A" P. 268-269
 Monument SET IRON FOR TRUE CORNER.
1912 - Curo, Book D' P. 147 - Find his 1906 B.T.s IRON CORNER
NOT BY R.R. END 1906 B.T.S - now stumps
1912 - also on microfilm - roll 115 BK 74 P. 64

Bearing Trees, Reference Objects

Species	<u>J. Pine</u>	<u>J. Pine</u>	_____
Diameter	<u>10"</u>	<u>8"</u>	_____
Bearing	<u>S33-27W</u>	<u>S29-30E</u>	_____
Distance	<u>22.80</u>	<u>36.30'</u>	_____

1906 ties

Evidence of Subsequent Corner Restoration

Year of search 1994 3-8 By Robert Murray
Placed 2"x30" square tube, w/ MnDOT cast
iron cap. Top of monument 0.3' above ground
4-26-94 Cert. Filed by: Robert Murray, RLS
15483, Doc #357119.

Bearing Trees, Reference Objects

<u>Norway</u>	<u>Norway</u>	<u>lavertole</u>	_____
<u>10"</u>	<u>10"</u>	_____	_____
<u>N32W</u>	<u>S61W</u>	<u>N72E</u>	_____
<u>53.76</u>	<u>35.25</u>	<u>5.79</u>	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

JUN 1996 R. DONAGHUE
PLAT SHOWS MON FOUND