


T. 145 R. 31 M. 5th Coordinates: X _____ Y _____
NE 33 Corner common to sections 27, 28, 33, 34



● = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875
Original monument Post

Original Evidence Found

Year of search 1900 by COE
Monument found _____
Lake Winnebigoishish Reservoir

Bearing Trees

Species	Jack Pine	Jack Pine	Jack Pine	Jack Pine
Diameter	4"	10"	10"	5"
Bearing	S 71° W	S 29° E	N 88° E	N 80° W
Distance	68 links	99 links	57 links	103 links

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1904 By T.M. Fowble
Location filed: Lake Winnebigoishish Reservoir
Monument:
Indicates known corner

Evidence of Subsequent Corner Restoration

Year of search 10/1912 By J.W. Curo, LS 1428
Location filed: Survey Record #216, Book A, page 529
Monument: Set 4"x 20" pine stake from GLO witnesses standing green and plainly marked as follows. J. Pine, S 69° W, 45.15', J. Pine, S 33° E, 65.61', J. Pine, N 68° E, 37.89', J. Pine, N 88°45' W, 68.25'

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Jack Pine	Jack Pine	Jack Pine	Jack Pine
Diameter	6"	6"	5"	6"
Bearing	S 88°45' E	N 12° W	S 60° W	N 63° E
Distance	4.44'	18.69'	18.7'	15.94'

Subsequent Corner Restoration

Year surveyed 7/1913 By J.W. Curo, LS 1428
Location filed: Survey Record #237, Book A, page 607
Monument: Set 2.5"x 4' iron pipe, capped with anchor rod pull up wood hub and replace with iron pipe, lists witnesses. 10" Jack Pine, S 47°30' W, 54.50' 5" Jack Pine, S 40°10' E, 64.72'

Evidence of Subsequent Corner Restoration Found

Year of search 4/2001 By CCHD/SO
Location filed: #2000.024
Monument: Found 2.5" ODIP down 0.6', 3'+/-, W. of centerline and 5'+/-, S. centerline. 6" Jack Pine, N 57° E, 84.80'(1981) 14" N. Pine, S 70° E, 77.68'(1981) 14" N. Pine, S 36° E, 100.55'(1981) 12" W. Pine, S 87° E, 47.23' 10" Jack Pine, N 36° W, 52.50' duple nail


6/1916, J.F. Pomasel, LS 1728
Curo Book 62, image 163
Level notes, indicate corner at 52+71.8.

5/1936, CCC
USFS Form 874-9
Notes witnesses as follows.
12" Jack Pine, East, scribed
12" Jack Pine, S E, scribed

5/1981, C. Krause, USFS
T145N R31W Field Book 1, page 14
Found 2.5"x 48" iron pipe, cap gone, drove down 6" on centerline, 15'+/-, S. of trail, E. and witnesses as follows.
13" Jack Pine, S 40° E, 64.7'(1913) 5' stub, 2 blazes
17" N. Pine, S 70° E, 77.68' spike in side
17" N. Pine, S 36° E, 100.55' spike in side
8" N. Pine, N 57° E, 84.80' spike in side
8" N. Pine, N 34° E, 83.93' spike in side

Index No. V 13

CASS COUNTY LAND CORNER RECORD



T. 14S R. 31 M. 5TH Coordinates: X _____ Y _____
NE 33 Corner common to sections 27, 28, 33, 34

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875
 Original monument Post

Original Evidence Found

Year of search _____ By _____
 Monument found _____

Species	Bearing	Trees	Distance
<u>J. Pine</u>	<u>J. Pine</u>	<u>J. Pine</u>	<u>J. Pine</u>
<u>4"</u>	<u>10"</u>	<u>10"</u>	<u>5"</u>
<u>S71W</u>	<u>S29E</u>	<u>N88E</u>	<u>N80W</u>
<u>68 LKS</u>	<u>99 LKS</u>	<u>57 LKS</u>	<u>13 LKS</u>

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1912 By JOHN CURD
 Location filed COUNTY SURVEY RECORD BOOK "A" P. 529-531
 Monument TWO OLD GAUT BITS; 4" J. PINE S70W
68 LKS, 10" J. PINE S29E 99 LKS, 10" J. PINE N88E
57 LKS, 5" J. PINE N80W 103 LKS SET 4x4x20" PINE
STAKE.

Evidence of Subsequent Corner Restoration

Year of search 1913 By JOHN CURD
 Book "A" P. 605-611 Find corner set in 1912 set
2 1/2 x 48" GALV. L.P. W/ CAP

Species	Bearing	Trees	Reference Objects
<u>J. Pine</u>	<u>J. Pine</u>	<u>J. Pine</u>	<u>J. Pine</u>
<u>6"</u>	<u>6"</u>	<u>5"</u>	<u>6"</u>
<u>S88-45E</u>	<u>N12W</u>	<u>S60W</u>	<u>N63E</u>
<u>4.44'</u>	<u>18.69'</u>	<u>187'??</u>	<u>15.94'</u>

Pomasei - 1916 - microfilm - roll 10S BK 62 P. 15
Find cor - dist to NE 28 = 5271.8'

Species	Diameter	Bearing	Distance
<u>J. Pine</u>	<u>J. Pine</u>	_____	_____
<u>10"</u>	<u>5"</u>	_____	_____
<u>S47-30W</u>	<u>S40-10E</u>	_____	_____
<u>54.50'</u>	<u>64.72'</u>	_____	_____

1913 ties

Subsequent Corner Restoration

Year surveyed 1981 By USFS
 Location filed _____
 Monument 2 1/2" ODIP, witness as follows:
6" J. Pine N57°E, 84.80' x
12" W. Pine S87°E, 47.23' x
14" N. Pine S70°E, 77.68' x
14" N. Pine S36°E, 100.55' x
x distance to 1 1/2" nail

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

4/01 CCSSO found 2 1/2" ODIP, down
0.6', 3' ± W. & and 5' ± S. &
1981 BT's good add the following:
10" J. Pine N36°W, 52.50' to dbl hd nail

Remonumentation certificate prepared _____ By _____
 Filed at _____ Date _____