


CERTIFICATE OF SURVEY

PART OF GOVERNMENT LOT 1, SECTION 18,
TOWNSHIP 140 NORTH, RANGE 28 WEST OF
THE 5th PRINCIPAL MERIDIAN
IN CASS COUNTY, MINNESOTA

PERIMETER SURVEY &
SUBDIVISION OF
TRACTS "A" - "G"



AMI SURVEYORS & MAPPERS
HC 74 BOX 1820, HACKENSACK, MINNESOTA 56452
PHONE: OFFICE (218) 682 2988 • RES. 682 2411
FAX 682 2988

INITIAL BEARING ASSIGNED

- DENOTES IRON MONUMENT FOUND
- DENOTES POWER POLE
- ▽ DENOTES LOWLAND

NOTE: The northwest corner of Government Lot 2 as shown hereon is not on a straight line between the southwest corner of Government and the lakeside marker between Sections 18 and 19. The northwest corner of Government Lot 2 is accepted as found and complies with the U.S. Bureau of Land Management policy set forth in their Instruction Memorandum 88-287. Referring to Section 6-28 of the Manual of Surveying Instructions 1973. Section 6-28 states, "Once it is accepted, a local point of control has all the authority and significance of an identified original corner...." This section is interpreted by this office (BLM), to pertain both to the reestablishment of lost corners and to the establishment/reestablishment of minor subdivision corners. In short, if you find a local corner that is set without gross error and recorded; or which has been accepted by all landowners, it can be accepted as a section corner, quarter corner, or "minor" subdivision corner. The result is often a "bent" subdivision line.

NOTE: TO THE BEST OF OUR KNOWLEDGE, THE LAYOUT OF TRACTS "A" THRU "G" SHOWN HEREON MEET THE REQUIREMENTS SET FORTH IN THE "CASS COUNTY SUBDIVISION AND PLATTING ORDINANCE" EFFECTIVE JANUARY 1, 1997.

THIS SURVEY WAS CONDUCTED IN ACCORDANCE WITH THE PROVISIONS OF MINNESOTA STATUTE 326.02, Subd. 4, IN CONFORMANCE WITH APPLICABLE SURVEYING STANDARDS SET FORTH IN THE "RECOMMENDED PROCEDURES FOR THE PRACTICE OF LAND SURVEYING", APPROVED AND ADOPTED BY THE MINNESOTA SOCIETY OF PROFESSIONAL SURVEYORS.

NOTE: NO ATTEMPT WAS MADE TO SURVEY AND SHOW THE EXISTENCE AND LOCATION OF WELLS, IMPROVEMENTS, UTILITIES OR VISIBLE FEATURES, EASEMENTS, ABOVEGROUND OR SUBSURFACE, TOPOGRAPHY, TERRAIN, LOW LAND LIMITS, ETC., EXCEPT AS SHOWN HEREON.

CERTIFICATE OF SURVEY

I, ROGER A. MUSTONEN, HEREBY CERTIFY THAT THIS SURVEY WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION AND THAT I AM A DULY REGISTERED LAND SURVEYOR UNDER THE LAWS OF THE STATE OF MINNESOTA.

ROGER A. MUSTONEN, LAND SURVEYOR
MINNESOTA LICENSE 11946

REVISED JANUARY 23, 1997

Roger A. Mustonen 1/23/97
ROGER A. MUSTONEN, LAND SURVEYOR
MINNESOTA LICENSE 11946

SYATA PERMIT APPLICATION 95-1083,
WOMAN LAKE (11-201P)
IN CASS COUNTY, MINNESOTA

LINE	BEARING	DISTANCE
L 1	N 26° 19' 27" E	55.00'
L 2	S 81° 17' 33" E	66.00'
L 3	S 19° 33' 27" W	52.00'
L 4	N 20° 24' 27" E	58.86'
L 5	S 10° 27' 27" W	72.66'
L 6	S 28° 35' 33" E	77.05'
L 7	N 68° 50' 33" W	19.73'
L 8	N 48° 30' 00" E	42.70'
L 9	S 10° 19' 40" E	2.25'
L 10	N 29° 40' 33" W	30.10'
L 11	S 40° 50' 25" W	33.00'
L 12	N 70° 36' 56" E	16.48'
L 13	N 64° 50' 54" W	19.60'
L 14	N 79° 17' 22" E	28.88'
L 15	S 38° 07' 33" E	33.00'
L 16	S 79° 17' 22" W	27.37'
L 17	S 38° 43' 44" W	33.00'

CURVE	DELTA ANGLE	RADI US	ARC	TANGENT	CHORD	CHORD BEARING
C 1	45° 29' 10"	50.00'	39.69'	20.96'	38.66'	S 42° 06' 19" E
C 2	38° 48' 21"	50.00'	33.88'	17.62'	33.23'	S 00° 02' 56" W
C 3	38° 32' 15"	50.00'	33.63'	17.48'	33.00'	S 38° 43' 44" W
C 4	128° 29' 28"	50.00'	112.13'	103.64'	90.07'	N 57° 45' 23" W
C 5	77° 21' 36"	50.00'	67.51'	40.03'	62.50'	S 19° 19' 04" W

SOUTHWEST CORNER OF GOVT LOT 1, SEC. 18, T.140N., R.28W. OF THE 5th P.M. 1089.57'

N 69° 02' 19" E 200.00'
S 69° 02' 19" W 200.00'
NORTHWEST CORNER OF GOVT LOT 2, SEC. 19-140-28

