

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


EAST QUARTER Corner of Section 6, Township 144, Range 30, 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

- On 8/25/81 found a GLO brass cap monument as set in 1930.
DATE
- left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



BEARINGS ARE APPROXIMATE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Gay H. Stevenson 9-11-82
SIGNATURE DATE

Registration No. 12684

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

264947
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 10:00 A.M. on the 14 day of Sept. A.D., 1982

County Recorder Bendah Hendrichs
By MS, Deputy

DOCUMENT NO. 264947

Statement of Evidence:

- 1875 U.S. General Land Office survey set wood post for this corner and marked the following bearing trees: 16" R. Oak S 68 W 170 links and 14" Sugar N 60 E 118 links.
- 1930 U.S. General Land Office dependent resurvey reestablished this corner by proportionate distance. No evidence was found of the original corner or bearing trees. An iron pipe with a marked brass cap was set to mark the corner. The following bearing trees were marked: 5" Ironwood S 40½ E 10 links and 6" Poplar S 44½ W 21 links.
- 1981 U.S. Forest Service technician C. Krause found the corner monumented with a GLO brass cap monument in good condition up 12". The following bearing trees were found: Ironwood snag on ground, well rotted, S 40½ E 6.6' and 14" Aspen with old scar and blaze S 44 W 13.9'. Area is to be clear cut and therefore set steel sign post as witness to monument 5.0' north, south, and west. A 4" x 4" x 5' cedar post was set alongside.
- 1982 County Surveyor's Records in the Recorder's Office were checked and no resurvey information was found on this corner.
- 1982 On Sept. 8 I visited the corner and found items as per the 1981 USFS reports. I accepted the monument as marking the same position as when set in 1930 by the GLO resurvey based on the bearing tree evidence.