

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

SOUTH QUARTER Corner of Section 31, Township 141 N, Range 31 W, 5th P.M.

STATE OF MINNESOTA, County of Cass


At the corner location shown on the sketch:

- On 9/11/84 found a 2½ inch by 5 foot long galvanized pipe with 3 inch DATE brass cap, stamped as shown, up 20 inches.
 - left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____ DATE

5¼° East declination

SKETCH OF REFERENCE TIES

not to scale



N 17°E, 120.7 ft. to a scribed
* 10 in. R. Pine with nail on side.
(1962) now a 12 in.


N 65°E, 86.3 ft. to
a scribed
14 in. J.
Pine.(1962) now a
dead snag.

N 61°E, 23.97 ft.

N 77°W, 6.77 ft. to a scribed
6 in. Birch with nail
on side.

to a scribed
6 in. Birch with nail on side.

8 ft. long metal fence post
with USFS signs no. 54-2 &
54-9.



8 ft. long metal fence post with
USFS signs no. 54-2 & 54-9.

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Anthony E. Keisch 12/12/84
SIGNATURE DATE

Registration No. 12266

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

280498
OFFICE OF THE REGISTER OF DEEDS

County of _____

I hereby certify that this document was filed in the Reg. of Deeds office at 10:15 A .M. on the 25 day of February A.D., 1985

Register of Deeds Claudine Kayler
County Recorder
By MS ,Deputy

DOCUMENT NO. 280498

Statement of Evidence:

SOUTH QUARTER CORNER OF SECTION 31, TOWNSHIP 141 NORTH,
RANGE 31 WEST OF THE 5th PRINCIPAL MERIDIAN.

1864 - The original public Land Survey was run by Johnson and Thornton. Set a wood post to mark the corner and recorded two bearing trees as accessories:

11" J. Pine N 37°W 19 links (12.54')
7" W. Birch N 48°E 12 links (7.92')

1921 - Elmer B. Horst Deputy Cass County Surveyor subdivided Section 31. Found no evidence of the original corner. Set corner by lost methods. Record Book C, page 445 & 456.

1963 - Peter J. Meyer R.L.S. found a 1-3/4" iron pipe marking the corner. He accepted corner as found and replaced iron with a 5' long galvanized iron with a 3 inch brass cap monument stamped with appropriate designations. Set new corner accessories: Certificate filed 7/3/63 Document # 160, in book of Corner Certificates in Cass County Recorder's office.

14" J. Pine N 65°E 86.3 ft.
10" R. Pine N 17°E 120.7 ft.
72" steel sign post N 80°E 4.15 ft.

1984 - Kerick surveying, Inc., Bemidji, MN. subdivided Section 31 for the U.S. Forest Service, found 3 inch stamped brass capped monument and accessories set by Meyer in 1962. The NE bearing tree is a dead snag. We accepted the location as found based on the fact that it fits with the lost position as set by Horst in 1921. Remarked Meyer accessories and set new accessories that appear on this certificate.