


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the Southeast One-sixteenth Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On May 16, 1985, to mark this corner position, we set a 5/8 inch diameter by 180 inch long aluminum rod with a 3.25 inch diameter aluminum tablet, containing a magnetized pellet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES
(not to scale)

compass decl: 5° E



N 8° E, 42.58 feet to a 16d nail in the southeasterly face of a 7.2 inch diameter Cedar.

N 21° W, 36.38 feet to a 16d nail in the southwesterly face of a 6.0 inch diameter Cedar.

8 foot long metal post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.



3.0 ft,

3.0 ft

8 foot long metal post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

S 23° E, 57.63 feet to a 16d nail in the southwesterly face of an 8.1 inch diameter Tamarack.

All bearing trees are double blazed and scribed "SE1/16 S9" and "BT", marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertical in the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn

Kenneth L. Whitehorn

Date Sep 26, 1985 Registration No. 14677

285580
OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 6 day of

Nov., 1985, at 10:30 A.M. and assigned DOCUMENT NUMBER 285580.

Clairine Kayler
County Recorder

ms

STATEMENT OF EVIDENCE: The Southeast One-sixteenth Corner of Section 9, Township 144 North, Range 25 West of the 5th Principal Meridian.

This corner position was not monumented at the time of the original survey of this township by Benjamin C. Baldwin, Deputy Surveyor, in 1876.

No record was found of establishment or visitation through the intervening years for this corner position. A thorough search was made of the area but no evidence of this corner location was found. Based on this information we established this corner position at the intersection of the East One-sixteenth Line and the South One-sixteenth Line of said Section 9. The basis for the determination of these subdivisional lines for this section are: Minnesota Department of Transportation (MN/DoT) Coordinate System, Roscoe Zone, North, 93-4700; coordinates on the corners of the Public Land Survey System. These coordinates were provided to the USDA-Forest Service (USFS) by Advance Surveying and Engineering Company, Minneapolis, Minnesota, under contract to perpetuate and restore the Public Land Survey System corners in this township.

We set the monument and witnesses as described and shown on the front of this document to perpetuate this corner position and establish National Forest Boundary.