

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **East Quarter Corner** of Section 19, Township 143 North, Range 26 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On April 23, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 60 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, up 18 inches and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)


decl: 5° E

N-44° W, 39.58 feet to a 16d nail in the northeasterly face of a 13.8 inch Tamarack, double blazed and scribed "1/4S19" and "BT".

N 65° E, 30.82 feet to a 16d nail in the southwesterly face of a 6.0 inch White Birch, double blazed and scribed "1/4S20" and "BT".

8 ft. steel post with a USFS 54-2 "PROPERTY BOUNDARY" sign attached.

3.0 ft



3.0 ft

8 ft. steel post with USFS 54-2 "PROPERTY BOUNDARY" and 54-9 "LAND SURVEY MONUMENT" signs attached.

S. 44° W, 23.83 feet to a 16d nail in the southeasterly face of a 7.9 inch Balsam Poplar, double blazed and scribed "1/4S19" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn

 Kenneth L. Whitehorn

Date JUN. 17 1986 Registration No. 14677

289674
OFFICE OF THE COUNTY RECORDER
 County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 1986, at 9:35 A.M. and assigned DOCUMENT NUMBER 289674.

Claudine Kaylor

 Claudine Kaylor, County Recorder
 ms

STATEMENT OF EVIDENCE: For the East Quarter Corner of Section 19, Township 143 North, Range 26 West of the 5th Principal Meridian.

This corner position was originally established on August 28, 1872 by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates the Mr. Griffin set a wood post to mark this corner position. This monumented corner position was referenced by: a 14 inch diameter Cedar that bears SOUTH 41 degrees EAST, a distance of 7 link (4.62 feet); and a 6 inch diameter Cedar that bears NORTH 40 degrees WEST, a distance of 8 links (5.28 feet).

Recorded on pages 81 thru 85 of County Survey Record Book B in the Office of the Cass County Recorder is a survey by John Curo, circa 1915. This record indicates that Mr. Curo found an old stake and: a downed Cedar, 14 inches in diameter, that bears SOUTH 41 degrees EAST, a distance of 7 links (4.62 feet); and a downed Cedar, 6 inches in diameter, that bears NORTH 40 degrees WEST, a distance of 8 links (5.28 feet). The record further states that Mr. Curo added: an 8 inch diameter Balsam that bears SOUTH 37 degrees 44 minutes WEST, a distance of 114.10 feet; and a 5 inch diameter Ash that bears NORTH 66 degrees WEST, a distance of 108.10 feet.

No other intervening records were found and our search of the area failed to uncover any evidence of the corner position. I feel that the 1915 Curo survey is the best evidence of this corner position and determined the obliterated position monumented from Mr. Curo's bearings and distances. This obliterated position was monumented and referenced as shown on the front of this document.