

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

For the **East Quarter Corner** of Section 20, Township 143 North, Range 26 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On April 29, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 36 inch long galvanized iron pipe, with a polystyrene base containing an embedded magnetized pellet, and topped with a 3 inch diameter brass tablet, flush with ground and stamped as shown in the sketch.

SKETCH OF REFERENCE TIES

Top of Page is NORTH

(not to scale)

decl: 5° E

N 66° E, 130.83 feet to a 16d nail in the northwesterly face of a 10.4 inch diameter Birch, base blazed and scribed "BT".

N 88° W, 133.98 feet to a 16d nail in the Southerly face of a 15.0 inch diameter White Birch, double blazed scribed "1/4S20" and "BT".



S 55° E, 172.61 feet to a 16d nail in the southerly face of a 11.6 inch diameter Red Oak, double blazed and scribed "1/4S21" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

Kenneth L. Whitehorn
Kenneth L. Whitehorn

Date JUN. 17 1986 Registration No. 14677

289675
OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of

June, 1986, at 9:40 A.M. and assigned DOCUMENT

NUMBER 289675.

Claudine Kaylor
Claudine Kaylor, County Recorder

STATEMENT OF EVIDENCE: For the East Quarter Corner of Section 20, Township 143 North, Range 26 West of the 5th Principal Meridian.

This corner position was originally established on August 29, 1872, by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that a wood post was set to mark this corner position. This monumented position was referenced by: a 6 inch diameter Fir that bears due WEST, a distance of 6 links (3.96 feet); and a 5 inch diameter Birch that bears NORTH 10 degrees EAST, a distance of 21 links (13.86 feet).

Recorded on page 162-163 of the County Surveyor's Record Book C in the Office of the Cass County Recorder is a James H. Flynn survey circa 1918. This record does not indicate that Mr. Flynn found any evidence of this corner position. Mr. Flynn referenced this corner position with the following new bearing trees: a 10 inch diameter White Pine that bears NORTH 88 degrees EAST, a distance of 76.5 feet; and a 5 inch diameter Aspen that bears NORTH 50 degrees WEST, a distance of 43.0 feet.

No other intervening record of visitation to this corner position was found. I feel that Mr. Flynn's 1918 survey measurements are the best evidence of this corner position and the position we monumented, as shown on the front of this document, is a prorated location using Mr. Flynn's bearings and distances between the Northwest and Southwest corners of Section 20.