

**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

For the **East Quarter Corner** of Section 29, Township 143 North, Range 26 West of the 5th Principal Meridian, STATE OF MINNESOTA, County of Cass.

On June 3, 1986, to mark this corner position, we set a 2.5 inch (outside diameter) by 24 inch long galvanized iron pipe containing an embedded magnetized pellet at its base, and topped with a 3 inch diameter brass tablet just below road surface and stamped as shown in the sketch.

**SKETCH OF REFERENCE TIES**


Top of Page is NORTH

(not to scale)

decl: 5° E

N 45° W, 134.74 feet to a 16d nail in the southwesterly face of a 14.4 inch White Oak with a single base blazed scribed "BT".

CSAH No. 65



S 72° W, 69.73 feet to a 16d nail in the southeasterly face of a 4.7 inch White Oak, double blazed and scribed "1/4S29" and "BT".

All bearing trees are marked with red enamel, a USFS 54-3 "BEARING TREE TAG", and a 60d spike driven vertically into the base of the baseblaze.

Statement of evidence relative to this corner position is on the back.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

*Kenneth L. Whitehorn*  
Kenneth L. Whitehorn

Date JUN. 17 1986 Registration No. 14677

<sup>289679</sup>  
**OFFICE OF THE COUNTY RECORDER**  
County of Cass

I hereby certify that this document was filed in the office of the County Recorder this 24 day of June, 1986, at 10.00 A.M. and assigned DOCUMENT NUMBER 289679.

*Claudine Kaylor*  
Claudine Kaylor, County Recorder

**STATEMENT OF EVIDENCE:** For the East Quarter Corner of Section 29, Township 143 North, Range 26 West of the 5th Principal Meridian.

This corner was originally set on August 27, 1872, by Eli W. Griffin, Deputy Surveyor, under contract to the General Land Office, now the Bureau of Land Management (BLM). The record of this survey is on file in the Office of the Secretary of State, St. Paul, Minnesota, and indicates that a wood post was set to mark this corner position. This monumented position was referenced by: a 8 inch diameter Birch that bears NORTH 32 degrees EAST a distance of 6 links (3.96 feet); and a 8 inch diameter Birch that bears SOUTH 13 degrees WEST a distance of 30 links (19.80 feet).

On record in the Office of the Cass County Recorder in SURVEYOR'S RECORD, Book C, page 151, is a record of a James H. Flynn survey from 1919. This record indicates that that Mr. Flynn set an iron monument at proportionate distance and referenced by: an 6 inch diameter Ironwood that bears NORTH 37 degrees EAST a distance of 47.30 feet; and an 12 inch diameter Elm that bears SOUTH 63 degrees WEST a distance of 38.50 feet.

No other record of visitation to this corner position was found and no physical evidence of this corner position was found during our search of the area. I feel that Mr. Flynn's 1919 survey information serves as collateral evidence and I reestablished a position for this corner using the fence line to the west for latitudinal control and prorated distances between recovered corners through the center of Section 29 to establish longitudinal control. We then monumented and referenced this position as shown on the front of this document.