CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
#11 Corner of Section 4 3 Township 141N, Range 26W, 5th P.M.	
STATE OF MINNESOTA, County of Cass	, , , , , , , , , , , , , , , , , , , ,
At the corner location shown on the sketch:	
$oxed{oxed}$ On $\frac{11-26-86}{\text{DATE}}$ found a $\frac{1\frac{1}{2}}{}$ Iron Pipe	
□ left monument as found, □ lowered monument, ☒ removed monument (explain)	
On 12-31-86 placed a 2" U.S.F.S. Iron Pipe with Brass Cap,	
*Magnetic: 4½°E. dec1. SKETCH OF REFERENCE TIES	
Based on Solar Observation 12-20-86	
S89½°W 12.08' to a 16d double headed nail in the south base of a 11" diameter blazed and scribed Ash. S13½°W 7.36' to a 16d double headed nail in the westerly base of a 4" diameter blazed and scribed Balsam. Monument is stamped T141N R26W MC S4 S3 1986 RLS 11946 RLS 11946	
Statement of evidence relative to this corner location is on back of page. $29.52.15$	
I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota. Reg. M. Johnson	OFFICE OF THE COUNTY RECORDER County of I hereby certify that this document was filed in the Co. Recorders office at 1:20 P. M. on the 23 day of february A.D., 1927 County Recorder Clandine Kaylon By MS Deputy
Date 2-23-87 Registration No. <u>11946</u>	DOCUMENT NO. 295215

Statement of Evidence:

During April of 1871, Walker, Allen and Putnam, under contract with the U.S.G.L.O. surveyed and marked the East, North and West lines of Township 141 North, Range 26 West of the 5th Principal Meridian.

From May 1, to May 10, 1871, Walker, Allen and Putnam, surveyed and marked the interior lines of the Township.

In 1936 USDA Forest Service personnel found the original bearing trees and set a $1\frac{1}{4}$ " X 48" iron pipe to perpetuate the corner position.

During the 1960's, according to local landowners, surveys were made in part of Section 4 by surveyors unknown, for the purpose of laying out lots and marking boundary lines.

In November of 1986, Roger A. Mustonen, RLS #11946, under contract with the USDA Forest Service, found the $1\frac{1}{2}$ " iron pipe monument, and accepts same as marking the Meander Corner # 11, and replaces it with a USDA Forest Service monument. (See other side for ties, ect.) During removal of the found monument, it broke in two pieces. The larger piece, $1\frac{1}{2}$ " X 32" was removed, leaving the shorter piece in the bottom.

Original G.L.O. survey set a wood post, from which: Cedar 10" N60W 13 1ks Cedar 10" S47E 7 1ks.

Decaying remnants of the trees still remain.