CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
Witness Corner to MeanderCorner of Sections 19 & 24Township 142N , Range 31W/30W, 5th P.M. (North Shores of Narrows) STATE OF MINNESOTA, County of Cass	
At the corner location shown on the sketch:	
DATE	pipe fitting bearing and distance from the
On 9/26/86 placed a Cass County 2 inch square iron monument, 3 feet long, with stamped cap over the 1/2 inch iron pipe.	
Declination: 6° East SKETCH OF REFERENCE TIES	
4	NOTE: all bearing trees have galvanized nail in side of base and two-part blaze with lower blaze scribed "BT".
Norway Pine, 11 inches in diameter, N60°W, 26.17 feet from corner 5 foot steel sign post, N42°W, 3.0 feet from corner.	Norway Pine, 8 inches in diameter, N2°E, 12.56feet from corner.
a	Corner Monument
Norway Pine, 7 inches in diameter, S74°W, 24.77 feet from corner	15±
	AGENCY BAY NARROWS
	OF LEECH LAKE
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.	OFFICE OF THE REGISTER OF DEEDS County of
	1 hereby certify that this document was filed in the Reg, of Deeds office at 11.50 A.M. on the
Registration No. 15483	22 day of <u>May</u> A.D., 19 82 Register of Deeds <u>landine Kaulo</u>
☑ Land Surveyor, ☐ Professional Engineer	By,Deputy
County Surveyor Cl County Engineer	DOCUMENT NO

M.H.D. FORM NO. 2105

Statement of Evidence: Witness Corner to Meander Corner Between Sections 19 and 24 T. 142 N., R. 30 and 31 W., 5th P.M.

- 1873

 U.S. General Land Office survey set a wood post for this corner and marked the following bearing trees: 24"
 Yellow Pine, N.49°E. 28 links (18.48 feet), 20" Yellow Pine, N.65°W. 11 links (7.26 feet).
- 1916 E.B. Horst found both original Government bearing trees and set a post for this corner. This information is recorded in County Book "C", page 523 and on Microfilm roll number 115, Book 80, page 42.
- General Land Office set a 1" x 36" iron pipe with brass cap for a Witness Corner to the Meander Corner.

 Evidence of the remains of the original bearing trees were found and the position for the Meander Corner being unsafe a Witness Corner was established with new references as follows: 10" White Oak, N.8 45"E.

 74 links (48.84 feet), 10" Norway Pine N.132 W. 53 links (34.98 feet).
- On September 26, Robert W. Murray, R.L.S., found a inch iron pipe fitting bearing and distance from found 1917 G.L.O. Norway Pine bearing tree. A County Monument was placed over the existing iron pipe and new references made as indicated on sketch.