CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
North Quarter Corner of Section 4 , Township 134 N., Range 32 W., 5th P.M.	
STATE OF MINNESOTA, County ofCASS	
At the corner location shown on the sketch:	
On 8/27/85 found q 2" I.P. , down 1', at intersection of roads N-S-E	
■ left monument as found, □ lowered monument, □ removed monument (explain)	
Onplaced a	
SKETCH OF REFERENCE TIES Not to scale	
-N- 11" Jack Pine	
N 23°W 74.46' 15" Jack Pine Twp. Road N 77°W 29.74' Power Pole S 55°W 63.05'	
Distances to nail in side of bearing object Bearings assumed using 5° declination	
Statement of evidence relative to this corner location is on back of page. 297514	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. White Lury 1-23-87 BIGNATURE DATE	OFFICE OF THE REGISTER OF DEEDS County of
Registration No. 11395 □ Land Surveyor, □ Professional Engineer	Register of Deeds Clouder Klayle By MS,Deputy
■ County Surveyor, □ County Engineer	DOCUMENT NO. 297514

STATEMENT OF EVIDENCE North Quarter Corner Section 4,T.134 N.,R.32 W.,5th

1858
U.S. General Land Office survey set a wood post for this corner and marked the following bearing trees: 10" Sp. Pine N 84°E 104 1ks., 10" Sp. Pine S 69°W 126 1ks.

1985 On August 27, Terry Freeman, Cass County Survey Technician, found a 2" I.P. down 1.0' at P.I. of roads N-S-E.

On July 29, Terry Freeman and Dan Gordon, left monument as found and marked bearings as shown on front of this certificate.

Although there is not a record of the 2" I.P. being set, the Cass County Surveyors Office feels that the I.P. is a perpetuation of the original corner and accepts it as such.