CERTIFICATE OF LOCATION	N OF GOVERNMENT CORNER
	3,Township <u>134 N.</u> , Range <u>32 W.</u> , <u>5th</u> P.M.
STATE OF MINNESOTA, County of CASS	
At the corner location shown on the sketch:	
13' N. of E-W centerline, inline w	.P. down 2.5',in centerline of N-S road, /N.edge of road E.
■ left monument as found, □ lowe	ered monument, 🖸 removed monument (explain)
On 7/29/86 placed a cast iron r	monument over capped I.P.
SKETCH OF F	REFERENCE TIES
Not to scale	
	#31
1	N 87°E 54.35'
Telephone Pedestal Post N 57°W 35.70'	"+" chisled on N.end of culver
Twp.	Road
	t"+" chisled on N.end of culver
	s '70°E 59.20'
	Rd
	· S
7	
Measurements are to mark in or on bearing Bearings are assumed using 5° declination	object.
Statement of evidence relative to this corner loc	cation is on back of page. 297517
hereby certify that this document and the data	OFFICE OF THE COUNTY RECORDER
contained herein was prepared by me or under	County of
my direct supervision.	I hereby certify that this document was filed in
Wall E. Com 1-23-87	the Co. Recorders office at 10155 A.M. on the
Registration No. 11395	County Recorder Claudin Konf
■ Land Surveyor, □ Professional Engineer	By m),Deputy
■ County Surveyor, □ County Engineer	DOCUMENT NO. 297 5/7

Statement of Evidence: Northeast Corner Section 3,T.134 N.,R.32 W.,5th P.M.	
1858	U.S. General Land Office survey set a wood post for this corner and marked the following bearing trees: 5" Tam N 7½°E 72 lks., 5" Tam. N 64°W 33 lks.,4" Tam. S 34°W 38 lks.,5" Sp.Pine S 85°E 149 lks.
1985	On August 27, Terry Freeman, Cass County Survey Technician found a 2" Capped I.P. down 2.5' in centerline of N-S road, 13' N. of E-W centerline and in line with N.edge of road E.
1986	On July 29, Terry Freeman and Dan Gordon set a cast iron monument over capped I.P. Top of monument is down 10".