

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Center Quarter Corner of Section 1, Township 141 N., Range 28 W., 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

On 7/14/87 found a 1" GLO brass cap monument
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



Not to scale

11" Burr Oak
 N 9°E 29.05'

15" Burr Oak
 N 24°E 46.60'

8" Burr Oak
 N 46°W 35.00'

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached.
 Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page. 301674

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter E. Lora 11-23-87
SIGNATURE DATE

Registration No. 11395

- Land Surveyor
 County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Lane

I hereby certify that this document was filed in the Co. Recorders office at 9:50 A .M. on the 16 day of Dec A.D., 19 87

County Recorder Claudia Kayler
 By ms, Deputy

DOCUMENT NO. 301674

Statement of Evidence: Center Quarter Corner Section 1, T.141.N., R.28 W., 5th P.M.

- 1919 US General Land Office dependent resurvey established this corner with a 1"x36" I.P. with marked brass cap. The following bearing trees were marked: .24" Red Oak S 29°W 81 lks., 20" Bl.Oak N 16 3/4°W. 87 lks.
- 1973 US Forest Service personnel found remains of the 1919 GLO survey. No new monument set, as GLO I.P. was in good condition. New BT's marked: 6"W.Oak N 46°W 35.00', 7" W.Oak N 8°W 29.65', 9" W.Oak N 36°E 47:40', all scribed "C₁ S1 BT", 6' steel sign post NORTH 5.00'. William Okerman filed CERTIFICATE OF LOCATION OF GOVERNMENT CORNER.
- 1987 Walt Curo, under Forest Service contract, found US GLO brass cap monument in place and 1973 Oak BT N 46°W. Marked new bearings as shown on front. He files this certificate to update the 1973 certificate.