CERTIFICATE OF LOCATION OF GOVERNMENT CORNER		
East Quarter Corner of Section 27 Township 141 N., Ronge 31 W., 5th P.M.		
STATE OF MINNESOTA, County of		
At the corner location shown on the sketch:		
☑ On 10/20/87 found a 2.3/4"x60" T.P. with brass cap		
☑ left monument as found, □ lowered monument, □ removed monument (explain)		
□ Onplaced a		
SKETCH OF REFERENCE TIES		
Not to scale		
- N -	12" Burr Oak E N 3°E 39.60' (New BT)	
10" Red Oak N 85°W 34.40 (C) (old BT)	8" Red Oak On 39°E 10.70' (old BT-dead)	
8" Red Oak S 53°W 34.89' (old BT)		
Trees double blazed,scribed,painted red and 54-3 Bearing Tree tag attached. Measurement taken to nail in side of tree.		
Statement of evidence relative to this corner loc	cation is on back of page. 302145	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.	OFFICE OF THE COUNTY RECORDER County of	
9/1/ Elm 12-26-87	I hereby certify that this document was filed in the Co. Recorders office at 3:30 P. M. on the Le day of A.D., 19 & 8	
SIGNATURE DATE Registration No. 11395	County Recorder Clandine Kaylan By MS, Deputy	
☐ County Surveyor	DOCUMENT NO. 302 145	

Statement of Evidence: Eas	t Quarter Corner Section 27,T.141 N.,R.31 W.,5th P.M.
1873	US General Land Office survey set a wood post for this corner and marked the following bearing trees: 5" Birch S 70 E 14 lks.,8" J.Pine stub N 71 W 17 lks.
1921	County Survey Record Book "C", page 460, shows a survey by E.B.Horst. He set the corner-a 2x48" I.M.
1922	County Resurvey plat in the Cass County Recorders Office cabinet "E", number 53, shows the corner as a 2x48" iron monument. Survey by E.B.Horst.
1959	Harold Curo found a 2x48" boiler flue and replaced it with a 2 3/4"x60" capped iron monument filled with concrete. He marked new BT's: 6" White Oak N 37-43 E 10.90',5" W.Oak N 83-20 W 33.70',7" Red Oak S 35 W 34.60'. He filed a Certificate of Location of Government Corner.
1980	US Forest Service personnel, Brama, Hare & Northe, found I.F. with brass cap and all 3 1959 BT's in good condition. Sign posts were set East & North of the I.P.
1987	Walt Curo, under Forest Service contract, found the I.P. and NW & SW 1959 BT's in good condition, NE BT is dead. Marked one new BT: 12" Burr Oak N 3 E 39.60'. I file this certificate to update the 1959 certificate.