

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Northeast Corner of Section 34, Township 141 N., Range 31 W., 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

On 10/20/87 found a 2 3/4"x60" I.P. with brass cap
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES

Not to scale

* 18" Norway Pine
N 43°W 76.46'
(1980 BT)

* 12" Burr Oak
N 55°E 51.90'
(1980 BT)

10" Red Oak
S 25°W 49.40'
(1959 BT)

* 20" Norway Pine
S 24°E 83.19'
(1980 BT)

Trees double blazed, scribed, painted red and 54-3 Bearing Tree tag attached.
Measurement taken to nail in side of tree.

Statement of evidence relative to this corner location is on back of page.

302148

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Walter E. Brown
SIGNATURE

12-26-87
DATE

Registration No. 11395

Land Surveyor

County Surveyor

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 3:50 P. on the 12 day of January A.D., 19 88

County Recorder Claudine Kayler

By MS, Deputy

DOCUMENT NO. 302148

Statement of Evidence: Northeast Corner Section 34, T.141 N., R.31 W., 5th P.M.

- 1873 US General Land Office survey set a wood post for this corner and marked the following bearing trees: 8" Pine N 70 W 18 lks., 8" Maple N 60 E 5 lks., 5" Lynn S 31 E 11 lks., 4" Birch S 42 W 24 lks.
- 1921 County Survey Record Book "C", page 468, shows a survey by E.B. Horst. He set a 2x48" I.M.
- 1922 County Resurvey plat in the Cass County Recorders Office cabinet "E", number 53, shows a 2x48" iron monument. Survey by E.B. Horst.
- 1928 County Resurvey plat in the Cass County Recorders Office cabinet "E", number 55, shows an iron monument at this corner. Survey by John Greene.
- 1959 Harold Curo found a 2x48" boiler flue for the corner. He set a 2 3/4"x60" capped monument and marked new BT's: 6" Red Oak S 21-27 W 48.75', 8" White Pine N 48-21 W 53.65', 24" White Pine N 36-34 E 58.50', all scribed with section number and "T141R31". he filed a Certificate of Location of Government Corner.
- 1980 US Forest Service personnel Brama and Schoonover found 1959 monument and SW BT standing. NW BT is a stub and NE BT is a snag. Marked 3 new BT's: 16" R. Pine N 36 W 76.34', 9" W. Oak N 59 E 51.85', 16" R. Pine S 20 E 83.08'. All scribed with section number and "T141N R31W BT". Steel sign posts 2.5' South and 1.9' West.
- 1987 On Oct. 20, Walt Curo, under Forest Service contract, finds the 1959 monument and SW BT and all 3 1980 BT's, all in good condition. I file this certificate to update the 1959 certificate.