

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER


NORTHEAST Corner of Section 31, Township 142, Range 28, 5th P.M.

STATE OF MINNESOTA, County of CASS

At the corner location shown on the sketch:

- On 10/15/87 found a 2" iron pipe monument with GLO brass cap top as set
DATE
in 1928.
 - left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



Spk in 14" Cedar
N 30 E 24.92



Spk in 6" Balsam
N 70 W 15.79'



Spk in 18" Cedar
S 40 E 81.15
(1916-BT)

BEARINGS ARE APPROXIMATE

Statement of evidence relative to this corner location is on back of page. 30420

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Joseph H. Atkinson 4/29/88
SIGNATURE DATE

Registration No. 12684

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE REGISTER OF DEEDS

County of Car

I hereby certify that this document was filed in the Reg. of Deeds office at 11:40 A.M. on the 6 day of May A.D., 1988

Register of Deeds Claudine Kayler

By MS, Deputy

DOCUMENT NO. 30420

Statement of Evidence:

- 1874 U.S. General Land Office survey set wood post for this corner and marked the following bearing trees: 20" Cedar N 61 W 13 links, 12" Cedar S 32 W 12 links, 20" Cedar S 55 E 23 links, and 8" Cedar N 19 E 35 links.
- 1916 County Surveyor's Record Book B, pages 391 to 398, show survey by John Curo. Notes show old stake and all 4 GLO bearing trees found. NW and SE trees alive and SW and NE trees down. A 4"x4"x48" Cedar Post and a 2"x48" iron were set and 4 bearing trees listed; 10" Tam. N 49 E 56.80', 20" Cedar N 63 W 8.50', 10" Cedar S 49-45 W 49.50', and 10" Cedar S 39-30 E 80.80'.
- 1928 U.S. General Land Office dependent resurvey found the corner marked by 2"x36" iron pipe and NW and SW original bearing tree stumps and local BT: 10' high Cedar stump S 39 E 27 links. An iron pipe with a marked brass cap was set to mark the corner. The following bearing trees were marked: 14" Tam. N 48 E 87 links, 14" Cedar S 9 E 30 links, and 10" Birch N 87 W 89 links.
- 1935 U.S. Forest Service records show the following: CCC corner report shows brass cap monument found and 5 bearing trees.
- 1970 Robert F. Schneider, RLS No. 5740, found GLO brass cap monument with 1½" iron pipe on south side and 6"x6" scribed cedar post. Notes show 12" Tam. stump N 48 E 57.42' with scribing clear and 10' high Cedar stump S 39 E 18'±.
- 1987 Found GLO brass cap monument, 1½ iron pipe, and cedar post as described by R.F. Schneider in 1970. Noted the following evidence of previous bearing trees:
- 1874 GLO BT - remains of cedar stump N 60 W 8.5'
 - 1928 GLO BT - remains of birch stump West 58.7'
 - 1916 Curo BT - cedar stump with scribing S 50 W 49.5'
 - 1928 GLO BT - fallen cedar S 10 E 19.8'
 - 1916 Curo BT - 18" Cedar (leaning) with scribing S 40 E 81.15'
 - 1928 GLO BT - Tamarack stump with scribing N 48 E 57.4'

Left monument in place and took new ties as shown on this certificate.