CERTIFICATE OF LOCATION OF GOVERNMENT CORNER		
North Quarter Corner of Section 15 Township 134 N., Range 31 W., 5th P.M.		
STATE OF MINNESOTA, County of _CASS		
At the corner location shown on the sketch:		
□ On found a		
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)		
On 10/23/86 placed a 2"x18" tele	spar monument with stamped aluminum cap din line with fence S.	
SKETCH OF REFERENCE TIES		
Not to scale		
Survey Marke NORTH 3	r Sign 0.0'	
¥	10" Red Oak N 49 E 117.95'	
P.P. N 52 W 54.60		
9" Burr Oak d S 22 W 70.23' 5' S 10 S 15 1986 1395	Twin 4" Ironwood S 45 E 85.67'	
Statement of evidence relative to this corner location is on back of page.		
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.    Walter   1-9-89   DATE   DATE	OFFICE OF THE COUNTY RECORDER  County of	
Registration No	By M.S DOCUMENT NO. 309798	

Statement of Evidence: North Quarter Corner Section 15, T.134 N., R.31 W., 5th P.M.	
1869	US General Land Office survey set a wood post for this corner and marked the following bearing trees: 4" Oak N 12 E 14 lks.,8" Aspen S 45 E 10 lks.
1986	On May 14, Terry Freeman, Cass County Survey Technician and Glen Williams, backhoe operator, dug in area of centerline of E-W road and fence South. Dug 10' E-Wx9' N-Sx4½'deep. 2½' road top-gravel and rocks,dug 2' into natural sandy-rocky-clay. Numerous loadstones and rocks. Found no evidence of corner.
1986	On Oct. 23, Terry Freeman and Land Dept. crew set 2"x18" telespar monument with aluminum cap down 1' in centerline of E-W road, in line with fence south, as determined by Comstock & Davis while surveying township roads in the area. Marked BT's as shown on front of this

certificate.