

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 35, Township 141N, Range 30W, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

Latitude:  $46^{\circ} 59' 13.510''$

Longitude:  $94^{\circ} 25' 42.393''$


On 6/28/88 found a 2" iron monument with brass cap (USFS)  
DATE

left monument as found,  lowered monument,  removed monument (explain)

On \_\_\_\_\_ placed a \_\_\_\_\_  
DATE

Magnetic Decl:  $5^{\circ}$  East SKETCH OF REFERENCE TIES  
Not to Scale

All distances are horizontal to nail in side of tree.



8" White Pine  
N 42 W 69.24'

9" White Pine  
N 6 E 57.47'

14" Norway Pine  
S 44 W 32.32'

Monument is located  
925' north of woods  
trail and 500' south  
of large swamp.  
8' sign post north 5.0'

Monument Stamped

T 141 N R 30 W

S 35 | S 36  
1965

All trees are painted with red enamel  
and marked with a 54-3 (bearing tree) tag.

R.L.S. No. 6807

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

David S. Landecker  
David S. Landecker  
Date 3/3/89 Registration No. 17008

OFFICE OF THE COUNTY RECORDER  
County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 1:10 P .M. on the 3rd day of April A.D., 1989

County Recorder Claudine Kaylor  
By BJK, Deputy

DOCUMENT NO. 31184

Statement of Evidence:

East Quarter Corner Section 35, Township 141  
North, Range 30 West, Cass County, Minnesota

X-21 141-30  
Bk.4 Pg.29

1873 P. H. Conger, U.S. Deputy Surveyor, originally established this corner position while subdividing Township 141 North, Range 30 West. The notes indicate a wood post was set to mark the corner position and the following witnesses: a 7 inch Maple North 68 degrees West a distance of 21 links; and a 4 inch Poplar North 80 degrees East a distance of 29 links.

1965 U.S. Forest Service technician James Ekstrom found the corner monumented with a 2 inch iron pipe. Set a 2 inch by 5 foot iron pipe with bronze cap for corner. The following bearing trees were marked: a 17 inch Norway Pine North 54 degrees West a distance of 37.6 feet; and a 16 inch Norway Pine North 63 degrees East a distance of 31.2 feet.

1965 U.S. Forest Service Surveyor Bill Okerman, Licensed Land Surveyor Number 6807, filed corner certificate using 1965 information.

1968 U.S. Forest Service Surveyor Bill Okerman, Licensed Land Surveyor Number 6807, filed a corner certificate on February 19, with the Cass County Recorder as certificate Number 644, using the 1965 information.

1986 U.S. Forest Service crews set an aerial target over this corner position for determination of coordinate values through the use of GPS on the Chippewa South Boundary Project Cadastral Survey U.S. Project Number 53-6392-8-219. This target allowed for the search and location of this corner. 1965 bearing tree was cut off.

1988 on June 28 a Landecker-Stevenson & Associates crew visited the corner and found the following evidence: a 2 inch iron pipe with brass cap up 18 inches with capped iron pipe, as previously used by the County, on west side; all 1965 bearing trees cut off. New bearing trees were marked as shown and steel sign post is in place as noted on front of this certificate.