CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
East Quarter Corner of Section 27 ,Township 134N. ,Ronge 31W. , 5th P.M.	
STATE OF MINNESOTA, County of	
At the corner location shown on the sketch:	
□ Onfound σ	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
on 9/18/86 placed a cast iron monument down 10"	
DATE	
SKETCH OF REFERENCE TIES	
NOT TO SCALE	
8- JACK PINE	
lus - min	
W N74 W - 30.05	
SURVEY MARKER A WEST 15.0	
SIGN	
(5)	Set.
33.3	
[ [m] 1 [ ]	
The JACK PINE	635. N
İ	12" BURR OAK
	"Year"
Statement of evidence relative to this corner location is on back of page. $319102$	
I hereby certify that this document and the data	OFFICE OF THE COUNTY RECORDER
contained herein was prepared by me or under	County of
my direct supervision.	I hereby certify that this document was filed in the Co. Recorders office at 4.05 M. on the
Wyt & las 3-15.90 SIGNATURE DATE	19  day of   Min  d
Registration No. 11395	County Recorder Clandine Kaylor  By M)  DOCUMENT NO. 319102
☑ Land Surveyor	By M), Deputy
™ County Surveyor	DOCUMENT NO. 317102

## Statement of Evidence:

T-17

East Quarter Corner, Section 27, T.134N., R.31W., 5th P.M.

- 1869 U.S. General Land Office survey set a wood post for this corner and marked the following bearing trees: a 6" Tamarack N75E 18 links and a 6" Spruce S82W 14 links.
- On May 16, Terry Freeman of the Cass County Surveyors Office and backhoe operator dug in the area of the north to south road and fence east. They dug an area 12' north to south by 8' east to west by 2' deep. The first 6" was top and fill and then they dug 1.5' into natural sand and gravel.
- On September 18, Terry Freeman and Norman Morris replaced a car spring that was found with a cast iron monument. It was placed down 10" and 3.5' west of the centerline of the north to south road and 8' north of the old fence to the east of the road.