

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 5, Township 140, Range 31, 5th P.M.

STATE OF MINNESOTA, County of Cass

At the corner location shown on the sketch:

On _____ found a _____
DATE


left monument as found, lowered monument, removed monument (explain)

On 6/4/90 placed a 2" tubular steel monument with aluminum cap
DATE

Magnetic Decl: 5° East
Not to Scale

SKETCH OF REFERENCE TIES

All distances are horizontal to nail in side of tree.



8" Red Oak
S 70 W 52.50'



12" Red Oak
S 28 W 23.31'



14" Red Oak
S 42 E 13.88'



Monument is located 100'± southerly of top of hill in woods.
Set a 8 foot steel sign post North 2.0'.

Monument Stamped
R31W
T141N
S 5 T140N
1990
RLS 17008

Statement of evidence relative to this corner location is on back of page. 325138

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Donald A. Sadak 11/15/90
SIGNATURE DATE

Registration No. 17008

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE REGISTER OF DEEDS
County of Cass

I hereby certify that this document was filed in the Reg. of Deeds office at 3:52 P.M. on the 21 day of November A.D., 19 90

Register of Deeds Claudine Kayler
By M.S., Deputy

DOCUMENT NO. 325138

North Quarter corner Section 5,
Township 140 North, Range 31 West, Cass
County, Minnesota

A-9 140-31

1870 Original survey did not establish this corner.

1980's Walt Curo, Registered Land Surveyor Number 11395, while surveying in Section 5, set an iron pipe for this corner.

1989 a Landecker-Stevenson & Associates, Inc., survey crew while surveying in Section 5, locate the Curo iron. The position does not check for the proportionate position between the Closing corner of Sections 5 and 6 as set on the 10th Standard Parallel and the Meander corner on the west shore of Ten Mile Lake.

6/4/90 a Landecker & Associates, Inc., Walker, Minnesota, survey crew set a 2 inch tubular steel monument with aluminum cap 100 feet southerly of top of hill in woods. Three new bearing trees were marked and a steel sign post set as noted on front of this certificate.