

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 33, Township 143N, Range 26W, 5th P.M.

STATE OF MINNESOTA, County of Cass


At the corner location shown on the sketch:

- On _____ found a _____
DATE
- left monument as found, lowered monument, removed monument (explain)
- On 4-24-90 placed a 2 inch x 54 inch Brass capped monument
DATE

Monument marked

SKETCH OF REFERENCE TIES

Not to scale



7 inch Maple
N 77° W
17.99 feet

Sec. 28

■
Sign post 4.5 feet

6 inch Maple
N 35° E
18.03 feet

○ — ■
Sign post 4.2 feet

10 inch Birch
S 70° E
13.01 feet

Sec. 33

All bearings true

All trees are scribed, painted with a 30d spike, and USFS 54-3 tag.

Statement of evidence relative to this corner location is on back of page. 325147

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.

William C. Clump

Date 11/14/90 Registration No. 17767

OFFICE OF THE COUNTY RECORDER

County of Cass

I hereby certify that this document was filed in the Co. Recorders office at 4:01 P. .M. on the 21 day of November A.D., 19 90

County Recorder Claudine Kaylor

By MJ, Deputy

DOCUMENT NO. 325147

Statement of Evidence:

V11 North quarter corner section 33

1/4 Cor. 28 and 33 (N 1/4 Cor. Sec. 33)

- 1872 U.S. General Land Office survey set wood post for corner and the following references were noted:
Birch 10" S 60 degrees E, 7 Links (4.62 feet)
Birch 6" N 28 degrees E, 12 Links (7.92 feet)
- 7-1916 J.H. Flynn, Cass County Surveyor, Survey Record No. 409, Page 161, lists corner post and the following new witnesses:
Maple 8" N 32 degrees E, 15 feet
Maple 12" S 8 degrees E, 31 feet
- 11-15-1989 Personnel from Kovanen & Osufsen Inc. chain to search area from section corner to west, find approximate corner tag set by C.K., no evidence of corner, or BT's found.
- 4-24-1990 Personnel from Kovanen & Osufsen Inc. traverse to search area, no further evidence of corner or BT's found. Then set a 2" x 54" brass capped monument midway and on line between the reestablished NE corner of section 33 and the recovered NW corner of section 33. The following witnesses were established:
Maple 6" N 35 degrees E, 18.03 feet
Maple 7" N 77 degrees W, 17.99 feet
Birch 10" S 70 degrees E, 13.01 feet
Set 8' long steel sign post with sign attached, East 4.2 feet
Set 8' long steel sign post with sign attached, North 4.5 feet

This position is not traceable to the original GLO corner, but accepted as corner for lack of further evidence.