



Meander Corner No. 6 of Section 26, Township 140 North, Range 29 West

The DNR Bureau of Engineering contacted the following for survey information:

Minnesota Secretary of State's Office  
Cass County Surveyor's Office  
Gary Stevenson, RLS, Walker, MN  
Walt Curo, RLS, Hackensack, MN  
Roger Mustonen, RLS, Hackensack, MN

- 1870 This corner was established by the U.S. General Land Office marked with a post and witnessed by the following bearing trees:  
N. Pine, 12" North 20° West, 28 links (18.48')  
W. Pine, 14" North 60° East, 37 links (24.42')  
Distance to the northeast corner Section 26 is 6.00 chains (396')
- 1936 Field notes of John W. Curo show a monument at the M.C. location being 384.3 feet south of an iron pipe at the section corner. Mr. Curo found the stump of the northeast W. Pine from a 2" x 12" hub and tack at the true M.C. The old northwest B.T. was gone. New ties were taken:  
Twin 4" W. Oak, North 44° 05' East, 22.98'  
10" W. Pine, North 32° 40' West, 34.22'
- 1954 Information from Cass County land corner records state that Harold Curo made note of a W.C. M.C. 10' north of the true M.C. The following bearing trees were referenced:  
N. Pine, 14" North 44° 33' West, 26.15'  
Twin W. Oak, North 67° 28' East, 17.30'  
R. Oak, 9" South 67° 50' East, 15.81'
- 1984 A field crew of the Department of Natural Resources, Bureau of Engineering, found a 1-1/2" iron pipe 7.7 feet north of the water's edge. Harold Curo's 1954 tie trees were still in place and the N. Pine and Twin Oak are the 1936 ties. A point computed from the 1936 ties is 10' south of the iron pipe.  
  
The 1-1/2" iron pipe is 385.89 feet south of the section corner.  
  
The iron pipe is accepted as a witness 10.0' northerly of M.C. 6.
- 1991 Ties were taken as shown on the face of this certificate.