

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner, Section 1, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

On January 30, 1997, Northern Lights Surveying and Mapping, Inc. monumented the "lost" quarter corner position relocated by single proportionate measurement between the northeast corner of T.142N., R.26W., and the Witness Corner to the Northeast Corner, Section 24, Township 142 North, Range 26 West.

SKETCH OF REFERENCE TIES & EVIDENCE


T.142N., R.26W.

T.142N., R.25W.

Section 1

NE 1

Section 8



NOT TO SCALE

0.102m Elm
N24°W
2.850m to 20d nail
in East face, up 0.350m
Scribed XBT
(1997)

N0°20'30"E
807.820m

0.203m Ash
N30°E
26.580m to 20d nail
in Northwest face, up 0.400m
Scribed S6 BT
(1997)

Steel Signpost
North
1.000m
Sign 54-9
(1997)

Bearings are Grid
North Minnesota
Central Zone, measured
with a hand compass
adjusted to 3°E East
declination.

Steel Signpost
East
0.610m
Sign 54-9
(1997)


N0°20'30"E
1236.212m

Aluminum Capped
Aluminum Rod
(1997)

0.152m Ash
S77°E
12.47m to 20d nail
in South face, up 0.800m
Scribed S6 BT
(1997)

NE 24

New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.



395045

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
LaVerne Leuelling Date

Registered Land Surveyor No. 16089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 2:52 P.M. Date: December 8, 1997

Recorder Claudine Kaylor

By K.J. Deputy

DOCUMENT NO. 395045

Statement of Evidence

Quarter Corner common to Section 6, Township 142 North, Range 25 West, and Section 1, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1871; General Land Office (G.L.O.) survey notes; Deputy Surveyors Walker, Allen, and Putnam set a wooden post for the quarter corner and referenced it with the following:

10" Aspen (0.254m)	10" Aspen (0.254m)
N28°E	S37°W
13 Links (2.615m)	23 Links (4.627m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; copies of these records are on file with the Cass County Surveyor's Office, Walker, Minnesota.

Winter 1996-1997; G.L.O. survey notes; Northern Lights Surveying and Mapping, Inc. used several feature calls made by Walker, et al in the original survey, along with United States Department of Agriculture-Forest Service (U.S.D.A.-F.S.) orthophotographs to establish a search area for the quarter corner.

January 30, 1997; Northern Lights Surveying and Mapping, Inc. crew of David Anderson and Joe Foster cruised to the quarter corner location, established, and GPS'ed two search positions. A search was also conducted at this time, but not conclusive G.L.O. evidence was found.

February 5, 1997; Northern Lights Surveying and Mapping, Inc. crew of David Anderson and Joe Foster traversed to the "lost" quarter corner position and conducted a search for original G.L.O. evidence, but none was found. The crew set the "lost" quarter corner between the northeast corner of T.142N., R.26W., And the Witness Corner of the Section corner common to Sections 18,19, 13, and 24, T.142N., R.25 and 26W. The crew noted that the position fell within an ash swale at the southeast corner of a beaver flowage. The monument established was a 1.219m long, 0.019m diameter aluminum rod with a 0.083m diameter aluminum stamped cap, up 0.200m. The crew also established the following references:

0.102m Elm	0.203m Ash	0.152m Ash
N24°W	N30°E	S17°E
2.650m to 20d nail	26.580m to 20d nail	12.47m to 20d nail
in East face, up 0.350m	in Northwest face, up 0.400m	in South face, up 0.600m
Scribed XBT	Scribed S6 BT	Scribed S6 BT
Steel Signpost	Steel Signpost	
East	North	
0.610m	1.000m	
Sign 54-9	Sign 54-9	

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #3, pp. 30-32.

Coordinates:

Cass County North:

Northing = 68,333.371 meters
Easting = 176,242.644 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 338,328.762 meters
Easting = 826,368.823 meters

Latitude = 47°08'37.16143" North
Longitude = 93°54'08.48764" West