


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner, Section 12, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

October, 1996; Northern Lights Surveying and Mapping, Inc. set a brass capped galvanized steel pipe at the "lost" position between the Witness Corner to the Northeast Corner of Section 24, and the Northeast Corner of Section 1.

SKETCH OF REFERENCE TIES & EVIDENCE



NOT TO SCALE

Bearings are Grid North Minnesota North Zone, measured with a hand compass adjusted to 3°E East declination.

0.250 Cedar
N15°W
25.029m
to 20d nail
in east face
up 0.49m
scribed S12BT
(1997)

Northeast Corner
Section 1
T.142N., R.26W.

0.250m Cedar
N38°W
31.173m
to 20d nail
in sw face
up 0.45m
scribed S12BT
(1997)

Steel Signpost
North 0.764m
Do Not Disturb
54-9
(1997)

T.142N., R.26W.
Section 12

T.142N., R.25W.
Section 7

Quarter Corner
1.219m long
0.051m diameter
galvanized steel pipe
0.053m diameter
brass cap
(1997)


New bearing trees were blazed, scribed & painted red. A tag stating the bearing & distance was affixed to the tree. A nail was placed in the base of the tree and the distance was measured from the monument to the nail.

0.180m Triple Cedar
S16°W
28.173m
to 20d nail
in west face
up 0.61m
scribed S12BT
(1997)

N0°20'30"E
2404.08

N0°20'30"E
2423.45

Witness Corner to
Northeast Corner Section 24
T.142N., R.26W.



395049

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

LaVerne Leuelling 11-16-97
LaVerne Leuelling Date

Registered Land Surveyor No. 18089
NORTHERN LIGHTS SURVEYING & MAPPING

OFFICE OF THE COUNTY RECORDER
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 3:02 P.M. Date: Dec. 8, 1997

Recorder Claudine Kaylor

By K.J. Deputy

DOCUMENT NO. 395049

Statement of Evidence

East Quarter Corner, Section 12, Township 142 North, Range 26 West, of the Fifth Principal Meridian, Cass County, Minnesota.

1871; General Land Office (G.L.O.) survey notes; Walker, Allan and Putman set a wooden post for the quarter corner and referenced it with the following:

10" Cedar (0.254m)	3" Cedar (0.076m)
S24°E	N14°W
10 Links (2.012m)	14 Links (2.816m)

Said records are on file with the Secretary of State, St. Paul, Minnesota; handwritten copies of these notes are on file with the Cass County Surveyor's Office, Walker, Minnesota.

June, 1963; U.S.D.A.-F.S. Field Book #2, p.24; U.S.D.A.-F.S. survey crew conducted a search in the area. This area had been burned over several years ago, and the crew found several old cedar stumps, but noted that it seemed that all evidence had been destroyed.

October, 1996; Northern Lights Surveying and Mapping, Inc. crew member Pete Berg cruised to the approximate corner location and established two Global Positioning System (G.P.S.) search points. A search was conducted at this time, and an approximate corner tag was located S18°W approximately 200'(60.960m). No evidence of the original survey was recovered, partially because the search area was bisected by a U.S.D.A.-F.S. road, and the area had been extensively logged.

May, 1997; Northern Lights crew of Joe Foster and Mike Sherek traversed to the lost quarter corner position and set a 1.219m long 0.051m diameter galvanized steel pipe with a 0.083m diameter brass cap up 0.30m, stamped, from which the following references were established:

0.180m Triple Cedar	0.250m Cedar	0.250 Cedar	Steel Signpost
S16°W	N38°W	N15°W	North 0.764m
28.173m	31.173m	25.029m	Do Not Disturb
to 20d nail	to 20d nail	to 20d nail	54-9
in west face	in sw face	in east face	
up 0.81m	up 0.45m	up 0.49m	
scribed S12BT	scribed S12BT	scribed S12BT	

Northern Lights Surveying and Mapping, Inc. Slater Township Field Book #2, p.56.

Coordinates

Cass County North

Northing = 66,717.693 meters
Easting = 176,232.412 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing = 336,713.15 meters
Easting = 826,360.19 meters

Latitude = 47°07'44.84784" North
Longitude = 96°54'09.28123" West