


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Section corner common to sections 32, 33, 4, and 5, Townships 143 and 142 North, Range 27 West, of the Fifth Principal Meridian, Cass County, Minnesota.

On September 17, 1998 Northern Lights Surveying and Mapping, Inc. found monument set by the General Land Office in 1920. One original bearing tree was found, and new BT's were established.

SKETCH OF REFERENCE TIES & EVIDENCE
T.143N., R.27W.



NOT TO SCALE



SECTION 32

SECTION 33

0.102m Aspen
N8°W
4.402m to 20d nail
up .300m
(1998)

0.102m Aspen
N2°E
3.743m to 20d nail
up 0.300m
(1998)

0.102m Aspen
S22°W
2.724m to 20d nail
up 0.300m
(1998)

0.102m Aspen
S83°E
4.782m to 20d nail
up 0.300m
(1998)

SECTION 5

SECTION 4

Red Pine stump
S65°E
25.930m to face

Bearings are Grid
North, Minnesota
Central Zone, measured
with a hand compass
adjusted to 3° East
declination.

New bearing trees were
blazed, scribed & painted
red. A tag stating the
bearing & distance was
affixed to the tree. A
nail was placed in the base
of the tree and the distance
was measured from the
monument to the nail.

T.143N., R.27W.

Statement of evidence relative to this corner location is on the back of this page

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Joseph Foster 5-14-99
Joseph Foster Date

Licensed Land Surveyor No. 25342
NORTHERN LIGHTS SURVEYING & MAPPING, INC.

OFFICE OF THE COUNTY RECORDER 412867
County of Cass

I hereby certify that this document was filed in the Recorder's office.

Time: 1:10 P.M. Date: May 17, 1999

Recorder Claudine Kaylor

By K.F. Deputy

DOCUMENT NO. 412867

Statement of Evidence

Page 2 of 2

Northeast Corner, Section 5, Township 142 North, Range 27 West, of the Fifth Principal Meridian, Cass County, Minnesota

September 1873, General Land Office (G.L.O.) survey notes; Deputy Surveyor William Allen set a wood post for the section corner and referenced it with the following:

8" Spruce	6" D. Fir	10" Ash	18" Oak
N11E	N81W	S72E	S33W
118 Links	13 Links	73 Links	40 Links

April 7, 1903; B.E.Trask of the U.S. Army Corps of Engineers, visited corner and noted 10" Ash BT was down and dead, and the other BT's were also badly decayed.

1920; Earl G. Harrington of the General Land Office found cedar stake and set an iron post, 3 ft. long, 2" diam., 26" in the ground with a brass cap for the corner. Harrington found evidence of stump holes from original bearing trees. New bearing trees were established:

10" Spruce	14" Pine	8" Tamarack	8" Pine
N31E	S62 1/2E	S40 1/2W	N5W
63 Links	129 Links	162 Links	139 Links

September 17, 1999; Northern Lights, Inc., crew of Leuelling and Heinle used Novatel GPS to cruise to corner. Monument was found in good condition. Also found 14" Pine stump BT from 1920 with scribing. Area had been logged off with young Aspen coming in. All four new BT's were scribed with (X) on face baze and (BT) on bottom blaze. BT's are as follows:

0.102M Aspen	0.102M Aspen	0.102M Aspen	0.102M Aspen	Red Pine stump
N2E	N8W	S22W	S83E	S65E
3.743m.	4.402m.	2.724m.	4.782m.	25.93m.
nail .3m up	nail .3m up	nail .3m up	nail .3m up	(1920)

Northern Lights Surveying and Mapping, Inc., Boy River Township Field Book #4, p. 60.

Coordinates:

Cass County North

Northing =89278.094 meters
Easting =160011.557 meters

State Plane Coordinate System
Minnesota Central Zone
NAD 83

Northing =339267.168 meters
Easting =810139.000 meters

Latitude =47°09'09".14480 North
Longitude =94°06'58".72503 West