


CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.


TERRY L. FREEMAN

Date: 12/14/06 License No: 21367
PLS #21367

OFFICE OF THE COUNTY RECORDER
County of CASS

I hereby certify that this document was filed in the Office of the County Recorder at _____ o'clock _____ M. on the _____ day of _____, 20____ A.D.

County Recorder _____

By: _____, Deputy
DOCUMENT NO. _____

EAST QUARTER Corner of Section 27, Township 142, Range 31, 5TH P.M.

On 6/30/05 found a FOUND 1" IP WITH GLO BRASS CAP UP 5"

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____

SKETCH OF REFERENCE TIES

Corner Index: T17

Not to Scale

MAG. DECL. 2° EAST



SECTION 27

CENTERLINE TRAIL

18'±



BLAZED 4" ASH W/DBL HEAD NAIL
IN EAST SIDE AND BT TAG

N 02° E
37.62

S 84° E
7.07

SECTION 26

17'±



BLAZED 5" OAK W/DBL HEAD NAIL
IN SOUTH SIDE AND BT TAG

FENCE

Statement of evidence for this corner position is on the back of this page

STATEMENT OF EVIDENCE

Index No. T - 17

East Quarter Corner, Section 27, Township
142 North, Range 31 West, Fifth Principal
Meridian

- 1873 P.H. Conger, U.S. Deputy Surveyor, originally established this corner position while surveying the interior subdivision lines of Township 142 North, Range 31 West. A wood post was set to mark the corner position with the following witnesses: A 4 inch Poplar, North 70 degrees East, 19 links; A 2 inch Poplar, South 31 degrees West, 28 links.
- 1915 E.B. Horst, County Surveyor, on microfilm of Curo notes Roll 11, Book 77 notes show he found stump of southwest bearing tree.
- 1921 A supplemental survey by General Land Office found no evidence of the original and set a 1 inch by 36 inch iron pipe with brass cap at the proportional position with the following witness: A 14 inch Norway Pine, North 78 degrees West, 158 links.
- 1925 Minnesota Highway Department right-of-way map-Walker to State Sanitarium-shows 2 inch iron pipe in place.
- 1967 August 15th, R.F. Schneider, RLS#5740, found GLO brass cap in place 17 feet North of fence East and South.
- 2002 Cass County Survey Office found monument in place.
- 2002 Certificate of Survey by Greg Fordham, RLS#19085, shows monument found.
- 2003 Certificate of Survey by Terry Freeman, RLS#21367, shows monument found.
- 2005 June, a Landecker & Associates, Inc. survey crew found the GLO brass cap monument and accepts it as a perpetuation of the proportional position as established by the General Land Office in 1921 from which the following accessories: A 5 inch Oak, South 84 degrees East, 7.07 feet; A 4 inch Ash, North 2 degrees East, 37.62 feet.

A000522175

**OFFICE OF COUNTY RECORDER
CASS COUNTY MINNESOTA**

**CERTIFIED, FILED, AND/OR
RECORDED ON
01/08/2007 03:53:11PM**

**AS DOC #: A000522175
PAGES: 2
REC FEES: \$0.00**

**KATHRYN M. NORBY
COUNTY RECORDER**

BY Kathryn M. Norby
DEPUTY