

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

WC to N1/4 corner of Section 06, Township 142 N., Range 30 W., 5th P.M.  
 State of Minnesota, County of Cass

At the corner location shown on the sketch:

On 12-06-2010 found a 1' iron pipe with a 2-1/2" GLO brass cap, 7" above surface grade.

left monument as found     lowered monument     removed monument (explain)

On \_\_\_\_\_ placed \_\_\_\_\_



## SKETCH OF REFERENCE TIES (NOT TO SCALE)



SECTION 31,  
T143N, R30W

Set New Tie:  
Set PK nail in easterly  
face of a 13" Oak.

Existing Tie:  
Found a doubleheaded nail in  
the westerly face of a 6" Spruce.

Set New Tie:  
Set PK nail in northerly  
face of a 12" Oak.

1/4 corner position  
14.52 feet East of  
brass cap monument

Existing Tie:  
Found a doubleheaded nail in  
the easterly face of a 22" Oak.

SECTION 6,  
T142N, R30W

Set New Tie:  
Set PK nail in westerly  
face of a 20" Oak.

Leech Lake

NOTE: All bearings are true.

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed land Surveyor under the laws of the State of Minnesota. I further certify that this United States public land survey monument record is correct and complete to the best of my knowledge and belief.

Terry L. Freeman, Land Surveyor

Date 12/9/11

MN License No. 21367

**A000578308**  
**OFFICE OF COUNTY RECORDER**  
**CASS COUNTY MINNESOTA**  
**CERTIFIED, FILED, AND/OR**  
**RECORDED ON**  
**03/01/2012 2:29:44 PM**  
**AS DOC #: A000578308**  
**PAGES: 2 REC FEES: 0.00**  
**KATHRYN M. NORBY**  
**COUNTY RECORDER**

Index No. A.0 - 2.9

**STATEMENT ON EVIDENCE**

**Witness Corner to the North Quarter Corner of Section 06, Township 142 North, Range 30 West of the 5th Principal Meridian.**

**In 1873**, P.H. Conger, U.S. Deputy Surveyor set a post to mark the North Quarter Corner and established bearing trees as follows: an 8" Red Oak, N16°E 30 links; a 6" White Oak, S51°W 34 links.

**1903 - 1904**, U.S. Army Corp of Engineers map for the Leech Lake Reservoir shows corner found by surveyor Horace Dunaway.

**In 1918**, Albinus N. Kimmel, U.S. Cadastral Engineer set a 1" x 36" iron post with brass cap in mound of stone for Witness Corner to the Quarter Corner and Meander Corner, 0.22 chains west of the true Quarter Corner determined from original bearing trees, now dead. He established new ties as follows: a 12" Oak, S 80° W 10 links; a 10" Oak, N 73-1/4° W 51 links. (Running notes on file in Cass County Survey Department)

**In August 1951**, Harold Curo found the brass capped monument. (Curo Book A, pages 18 & 22) Sketch on page 26 shows Witness ¼ corner U.S. brass cap.

**In June 1955**, Harold Curo found the brass capped monument. (Curo Book A, Pages 56 & 59)

**In September 1958**, Harold Curo found the brass capped monument. (Curo Book A, pages 72 & 74)

**In March 2004**, a Landecker & Associates survey crew found the brass capped monument. (Records on file with Northern Engineering)

**In December 2010**, a Northern Engineering & Consulting survey crew found a 1" iron pipe with a 2-1/2" GLO brass cap, 7" above surface grade with rocks around base. Two existing ties were found and two new ties were set as shown on the front page of this certificate. Northern Engineering & Consulting, Inc. accepts the brass cap as the witness to the ¼ corner as established by the GLO in 1918.

**Minnesota State Plane (Central Zone)**

Northing 1112603.796  
Easting 2557279.923

**County Coordinates (Cass County North)**

Northing 226858.658  
Easting 424316.143

