



A000583881

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

9/7/2012 1:16:15 PM

AS DOC #: A000583881

PAGES: 3

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY KF Dep

## AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO A CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

STATE OF MINNESOTA }

COUNTY OF CASS }

} ss

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;





-2-

That in order to make the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 30 day of August, 2012.

Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

**CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

Corner to Secs. 31-6 T. 138 N. &amp; 137 N. R. 29 W.

State of Minnesota, }  
 COUNTY OF CASS } ss.

I hereby certify that on the 16th day of May 1922

I found the  $\frac{1}{4}$  corner of Sec. 31-6, T. 137 & 138 N., R. 29 W.

which was evidenced by 8" Jack Pine SW 26.15 feet - 8" Jack Pine W. 32.8 feet.

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 6" round concrete monument already placed

I further certify that I established Two (2)

reference or witness monuments consisting of 2 hollow iron pipes 3' 6" long

which reference or witness monuments are located in the manner following:

2" iron pipe SW 46.7 feet

2" " " NW 46.7 "

These pipes are four inches above the level of the ground

Pine River  
Dated at ~~Walker~~ this 17th day of May 1922

C. J. BARK

C. J. BARK  
Ass't. ~~County Surveyor~~ Highway Engineer

OFFICE OF REGISTER OF DEEDS, }  
 COUNTY OF CASS }

I hereby certify that the within instrument was filed in this office for record on the 9th day of Nov. A. D. 1922 at 9 o'clock and was duly

Recorded in Book 1 of \_\_\_\_\_ on page \_\_\_\_\_

By *Orlin N. ...* Deputy.

