

A000587670

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

12/26/2012 2:01:25 PM

AS DOC #: A000587670 PAGES: 4 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER

BY_MW___Dep

AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me

this 26th day of 18C, 20/2.

Notary Public

ROBERT H. YOCHUM Notary Public State of Mannesola My Comm. Esp. 1-31-20(5)

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

S.M.C.	on the	reestablished	original	meander line	12.70	chains	south	of the	ouarter
Corner	to Sec	s8 - 1 7	<i>T.</i>	ll N			29 M		22/

State of Minnesota, County of Cass

Poter J. Meyer , being first duly sworn, deposes and says:

That I reside at Cass Lake , Minnesota , and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628

I further depose and say that on the lith day of February , 19 63 ,

I found the Special Meander corner of Section 17

which was evidenced by the remains of the G.L.C. resurvey of 1918.

Corner was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch diameter iron post with a bress cap stamped:- Carper was found to be marked by a 1 inch

from which reference or witness monuments are located in the manner following:

Maple 5 inch \$33°W 16.8 feet marked SMC BT Cak 7 inch \$56°E 13.85 feet marked SMC BT Steel sign post 72 inches long, set 2h inches in ground with standard signs 5h-2 and 5h-4 attached \$76°E 3.85 feet.

bearing and distance with blaze facing corner.)

All reference bearings are true bearings.

(Surveyor's Signature)

In the Presence of:

Sullah Hendrick

Subscribed and sworn to before me at

Walker, Minnesota

this 16 day of September 19 63

Deputy Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 16

day of September A.D., 19 63

at 9 o'clock A.M.

Leonard P. Pettrion

Register of Deeds

By Bulah Kindrick Deputy



Page 4 of 4 A000587670

