



**A000588025**

**OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON**

**12/28/2012 11:31:08 AM**

**AS DOC #: A000588025**

**PAGES: 4**

**REC FEES: 0.00**

**KATHRYN M. NORBY  
CASS COUNTY RECORDER**

**BY KF Dep**

Page 1 of 4 A000588025

## **AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO A CERTIFICATE OF LOCATION OF GOVERNMENT CORNER**

STATE OF MINNESOTA     }  
  }ss  
COUNTY OF CASS         }

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



-2-


That in order to make the attached CERTIFICATE OF LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me  
this 27th day of DEC, 2012.

Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

Corner to Sec. 31 T. 141 R. 31 No. 29

**State of Minnesota,** }  
 COUNTY OF CASS } ss.

I hereby certify that on the 19th day of April 1959

I found the S.M.C. corner of 252.70 ft S of center Sec 31

which was evidenced by a 2x48 inch boiler flue

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 2 3/4 x 60 inch capped monument filled with concrete

I further certify that I established ~~Bearing Trees~~  
 reference or witness monuments consisting of ~~Trees~~

which reference or witness monuments are located in the manner following:

a White Pine tree 14 inches in diam bears S 3°19' E 32.20 ft Mkd S.31 T.141 R.31

a Spruce tree 14 inches in diam bears S 75°30' E 3.90 ft Mkd S.31 T.141 R.31

a Spruce tree 8 inches in diam bears N 8°11' W 2395 ft Mkd S. 31 T.141 R.31

Dated at Walker this 19th day of April 1959 ~~192~~

*Harold C. ...*

County Surveyor or Highway Engineer


**OFFICE OF REGISTER OF DEEDS,** }  
 COUNTY OF CASS }

I hereby certify that the within instrument was filed in this office for record on the 22 day of March A. D. 1959 at 9 o'clock a M., and was duly Recorded in Book of on page

*L. P. Peterson*

Register of Deeds.

By *Beulah Gevaier* Deputy.





Section 31 Township 141<sup>N</sup> Range 31<sup>W</sup> of the 5<sup>th</sup> P.M.

