

A000590051

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

2/26/2013 1:37:03 PM
AS DOC #: A000590051
PAGES: 4
REC FEES: 0.00
KATHRYN M. NORBY
CASS COUNTY RECORDER
BY KF _____ Dep

AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

STATE OF MINNESOTA	}
	}ss
COUNTY OF CASS	}

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;

-2-

That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me

this 26th day of Jeb.

, 20<u>.13</u>

SUSANNE GRAY
Deputy Auditor, Cass County Minnesota
Notarial Officer (ex-officio notary public)
My term is indeterminate

Notary Public

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

I further depose and say that on the lst day of July ,1966 found the Quarter corner of Section's 17-20 which was evidenced by G.L.O. resurvey of 1937 a set iron post 3 feet long 1 inch diameter with brass cap marked 1 S 17 4 \$\overline{5}\$ inch \$\S9\frac{1}{4}^0\text{E}\$ 25 links or 16.50 feet - Now a Birch stump at correct bearing and distance - scribe visible. Sedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	Quarter Corner to Sec. 's 17-20	<i>T</i> . 11/1N	R. 27W	No. 408
William H. Okerman , being first duly sworn, deposes and says: That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under a laws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807. I further depose and say that on the lst day of July , 19 66 found the Quarter corner of Section's 17-20 which was evidenced by G.L.O. resurvey of 1937 a set iron post 3 feet long 1 inch diameter with brass cap marked 1 S 17 S 20 Sirch 5 inch S94° E 25 links or 16.50 feet - Now a Birch stump at 1937 correct bearing and distance - scribe visible. Sedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	State of Minnesota,			
That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under to aws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807 I further depose and say that on the lst day of July , 19 66 found the Quarter corner of Section's 17-20 which was evidenced by G.L.O. resurvey of 1937 a set iron post 3 feet long 1 inch diameter with brass cap marked 1 S 17	County of Cass	88.		
That I reside at Bemidji , Minnesota , and am registered as a Land Surveyor under the saws of the State of Minnesota, having Surveyor's Registration Certificate No. 6807. I further depose and say that on the lst day of July , 19 66 found the Quarter corner of Section's 17-20 which was evidenced by G.L.O. resurvey of 1937 aset iron post 3 feet long 1 inch diameter with brass cap marked 1 S 17	William H. Ok	erman , b	eing first duly sworn, depo	ses and says:
I further depose and say that on the lst day of July ,1966 found the Quarter corner of Section's 17-20 which was evidenced by G.L.O. resurvey of 1937 a set iron post 3 feet long 1 inch diameter with brass cap marked 1 S 17 4 \$\overline{5}\$ inch \$\S9\frac{1}{4}^0\text{E}\$ 25 links or 16.50 feet - Now a Birch stump at correct bearing and distance - scribe visible. Sedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	That I reside at Bemid	ji Minnesota	, and am registered as a L	and Surveyor under the
found the Quarter corner of Section's 17-20 which was evidenced by G.L.O. resurvey of 1937 set iron post 3 feet long 1 inch diameter with brass cap marked 1 S 17 4 S 20 Birch 5 inch S94°E 25 links or 16.50 feet - Now a Birch stump at 1937 correct bearing and distance - scribe visible. Gedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.				
which was evidenced by G.L.O. resurvey of 1937 a set iron post 3 feet long 1 inch diameter with brass cap marked Birch 5 inch S94°E 25 links or 16.50 feet - Now a Birch stump at correct bearing and distance - scribe visible. Cedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	I further depose and say tha	t on the lst	day of July	, 19 66
Sirch 5 inch S94°E 25 links or 16.50 feet - Now a Birch stump at 1937 correct bearing and distance - scribe visible. Sedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	found the Quarter	corner of Section!	s 17 - 20	
Sirch 5 inch S94°E 25 links or 16.50 feet - Now a Birch stump at 1937 correct bearing and distance - scribe visible. Sedar 16 inch N11°W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	which was evidenced by G.L.O.	resurvey of 1937		
Sirch 5 inch $59\frac{1}{4}$ E 25 links or 16.50 feet - Now a Birch stump at correct bearing and distance - scribe visible. Sedar 16 inch N11 $^{\circ}$ W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	set iron post 3 feet long	l inch diameter with	brass cap marked	1 S 17
correct bearing and distance - scribe visible. Sedar 16 inch Nll ^O W 80 links or 52.80 feet - Now a Cedar stump at correct bearing and distance - scribe not visible.	Sirch 5 inch S9 ¹⁰ E 25 links	or 16.50 feet - Now a	Birch stumo at	
at correct bearing and distance - scribe not visible.	correct bearing and dista	nce - scribe visible.		-/31
at correct bearing and distance - scribe not visible.	ladam 16 dmah N170N 80 Jdml		- O-Jon	
and that to perpetuate the location of such corner I did, at the exact location thereof place a normanent mani-	_			
, , , but the court of the cour	and that to perpetuate the location	n of such corner I did, at th	e exact location thereof, pla	ce a permanent marker
onsisting of no new marker set, used G.L.O. brass cap.	onsisting of no new marker s	et, used G.L.O. brass	cap.	

Birch 8 inch S21°E 16.6 feet - scribed $\frac{1}{4}$ S20 BT.

Elm 7 inch N28 $^{\circ}$ W 34.0 feet - scribed $\frac{1}{4}$ S17 BT.

Set a steel sign post 72 inches long with signs 54-2 and 54-4 attached due West 2.8 feet.

All reference bearings are true bearings.

William Walerman
(Surveyor's Signature)
In the Presence of:
Bulah Heridrick
Clarida Hay In
Subscribed and sworn to before me at
Walker, Minnesota
this 17 day of Neventer 19 66
Bulak Hendrice
Register of Deeds, Cass County, Minn.

OFFICE	UF	REGISTER	OF.	DEEDS	
County	of	Cass			

I hereby certify that the within instrument was filed in this office for record on the 17 Mendricks Register of Deeds



Page 4 of 4 A000590051

