




That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me this 27th day of Feb., 2013.

Notary Public



This instrument was drafted by:

Robert Kovanen
Cass County Surveyor
P.O. Box 579
Walker, MN 56484

AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec.'s 5 - 6 - 7 - 8 T. 145 N. R. 27 W. No. 195

State of Minnesota, }
 County of Cass } ss.

Peter J. Meyer, being first duly sworn, deposes and says:

That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628.

I further depose and say that on the 15th day of May, 1963, I found the section corner of sections 5 - 6 - 7 - 8 which was evidenced by two bearing trees from the original Government Survey of 1873. Norway pine 28" N29°E 14 links or 9.24 feet (Now a 28 inch pine windfall scribed "T145R27 S8" at S29°E and record distance) Norway pine 24" S79°W 50 links or 33.00 feet (Now a 26 inch pine stub S79°W 42.0 feet badly burned with blaze facing corner.)

A squared wood post was found marking corner.

and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch inside diameter, 5 foot long, galvanized wrought iron pipe filled with concrete and capped with a 3 inch diameter bronze tablet stamped:-

T145N	R27N
S6	S5
S7	S8

1963

RLS No. 3628

from which reference or witness monuments are located in the manner following:

Red pine 15 inch N73°E 21.2 feet marked S5 BT

Red pine 11 inch S74½°E 72.4 feet marked S8 BT

Cedar 4 inch S38½°W 29.5 feet marked S7 BT

Red pine 6 inch N28°W 62.9 feet marked S6 BT

Steel sign post 72 inches long, set 24 inches in ground with signs 54-2 and 54-4 attached due West 4.6 feet.

All reference bearings are true bearings.

Peter J. Meyer
 (Surveyor's Signature)

In the Presence of:

Beulah Hendrick

Jane Ann Nelson

Subscribed and sworn to before me at

Walker, Minnesota

this 16 day of September, 1963

Beulah Hendrick

Notary Public

Deputy Register of Deeds, Cass County, Minn.

OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 16

day of September A.D., 1963

at 9 o'clock A.M.

Leonard P. Peterson
 Register of Deeds

By *Beulah Hendrick* Deputy



SECTION _____ TOWNSHIP _____ RANGE _____ P.M.

