





-2-

That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me this 27<sup>th</sup> day of Feb., 2013.

Notary Public



This instrument was drafted by:

Robert Kovanen  
Cass County Surveyor  
P.O. Box 579  
Walker, MN 56484

## AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER

Corner to Sec. 20-21-28-29 T. 145 N R. 27 W No. 22

State of Minnesota, }  
 County of Cass } ss.

Peter J. Meyer, being first duly sworn, deposes and says:  
 That I reside at Cass Lake, Minnesota, and am registered as a Land Surveyor under the laws of the State of Minnesota, having Surveyor's Registration Certificate No. 3628

I further depose and say that on the 3rd day of December, 1958, I found the section corner of sections 20-21-28-29

which was evidenced by one remaining original bearing tree, and two remaining B.T.s from recovery survey by J. A. Gjelhaug, Jr., Civil Engineer, U. S. Forest Service, in 1937.  
 (1) 4 inch Spruce (now stump mostly decayed with no scribing visible) S 77° W, 26 links or 17.2 feet.

On file in Forest Supervisor's Office, Cass Lake, Minnesota: Found scribed spruce stump from which he set scribed 3 inch x 3 inch post and set the following bearing trees, 6 inch Balsam (now 8 inches with scribing visible) N 52° W, 20.5 feet; 9 inch Cedar (now 10 inches with no scribing visible) N55°E, 17.8 feet.

A check showed no evidence of the original Gov. corner or other original Gov. bearing tree. and that to perpetuate the location of such corner I did, at the exact location thereof, place a permanent marker consisting of a 2 inch inside diameter, 5 foot long galvanized wrought iron pipe filled with concrete and capped with a 3 inch diameter bronze tablet stamped:

T 145 N R 27  
 20-21-28-29  
 1958  
 R.L.S. 3628

from which reference or witness monuments are located in the manner following:

8 inch	W. Birch	N 27° W	25.4 feet
10 inch	W. Spruce	S 33° W	29.0 feet
10 inch	Balsam	S 21½° E	30.1 feet
9 inch	Cedar	S 86° E	34.3 feet

All reference bearings are true bearings.

*Peter J. Meyer*  
 (Surveyor's Signature)  
 In the Presence of  
*Beulah Kerner*  
*P. Peterson*  
 Subscribed and sworn to before me at  
 Walker, Minnesota  
 this 11th day of June, 1960  
*Beulah Kerner*  
 -Notary Public-  
 Deputy Register of Deeds:

## OFFICE OF REGISTER OF DEEDS

County of Cass

I hereby certify that the within instrument was filed in this office for record on the 11th day of June, A.D., 1960 at 9 o'clock AM.

*Leonard P. Peterson*  
 Register of Deeds

By Deputy



SECTION \_\_\_\_\_ TOWNSHIP \_\_\_\_\_ RANGE \_\_\_\_\_ P.M. \_\_\_\_\_

