

4000590411

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

3/1/2013 12:37:27 PM
AS DOC #: A000590411
PAGES: 4
REC FEES: 0.00
KATHRYN M. NORBY
CASS COUNTY RECORDER
BY SR Dep

AFFIDAVIT BY THE CASS COUNTY SURVEYOR IN REGARD TO AN AFFIDAVIT AS TO LOCATION OF A GOVERNMENT CORNER

STATE OF MINNESOTA }

ss

COUNTY OF CASS }

Robert Kovanen, being first duly sworn, deposes and states as follows:

That Affiant is the County Surveyor in and for the County of Cass, in the State of Minnesota;

That in such capacity Affiant has knowledge of the books and records kept in the Office of the County Surveyor in and for the County of Cass, State of Minnesota;

That the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER has been found in the Surveyor's records and after checking with the Cass County Recorder, it was determined that the document was never assigned a document number and was never officially recorded in the real estate records or tracted in the tract indexes within said Cass County Recorder's Office;



That in order to make the attached AFFIDAVIT AS TO LOCATION OF GOVERNMENT CORNER a matter of public record and locatable by legal description, Affiant does herewith attach said document to this affidavit and requests the Cass County Recorder to record same at her earliest opportunity.

FURTHER, Affiant sayeth not.

Robert Kovanen, Cass County Surveyor

Subscribed and sworn to before me

this 37 day of February, 2013.

Notary Public

LINDA C. HUSBY

Notary Public

State of Minnesota
My Comm. Exp. 1-31-2015

This instrument was drafted by:

Robert Kovanen Cass County Surveyor P.O. Box 579 Walker, MN 56484

AFFIDAVIT	AS	TO	LOCATION	\mathbf{OF}	GOVERNMENT	CORNER
------------------	----	----	----------	---------------	-------------------	---------------

	o Sec314		T. 145N	R29W	No. 583
State o	f Minnesota,	. (
County of	Cass	\int^{88} .			
	William H. (Okerman	, be	ing first duly sworn, depose	s and says:
That I r	$eside\ at$	B emidji	, Minnesota	, and am registered as a Lar	nd Surveyor under the
laws of the S	tate of Minneson	ta, havi <mark>ng</mark> Su	rveyor's Registratio	on Certificate No. 6807	
I further	r depose and say	that on the	7th	day of July	, 19 69 ,
found the	Standard Qua	arter corner	of Section 34		
which was evi	idenced by ren	nains of the	e original Gover	nment survey of 1874. N5 ^O W 25.00 feet with	
Y. Pine	8 inch N36°E visible.	38.28 fee	t - now R. Pine	24 inch N36°E 34.00 fo	eet with scribe
capped w	ith a 3 inch	diameter br	rass tablet stam	ped:	S.C.
capped w	160 a 3 inch	css monument	rass tablet stamp s are located in the stampet scribed SC $rac{1}{4}$ S	ped: manner following:	
rom which ron N. Pine	ich a 3 inch eference or witne 22 inch N46 ⁰ W	ess monument 65.20 fee	rass tablet stamp	ped: manner following: 534 BT	S.C. T145N R29₩ ¼ S34 1969
from which row Pine N. Pine	ich a 3 inch eference or witne 22 inch N46 ⁰ W	ess monument 65.20 feet	rass tablet stamper s are located in the set scribed SC $\frac{1}{4}$	ped: manner following: 534 BT	S.C. T145N R29₩ ¼ S34 1969
from which row N. Pine N. Pine Elm 8 in	eference or witne 22 inch N46°W 19 inch N1°E ch S37°E 8.6	ess monument 1 65.20 feet 45.90 feet	rass tablet stamper s are located in the set scribed SC $\frac{1}{4}$ Scribed SC $\frac{1}{4}$ Scribed SC $\frac{1}{4}$ Scribed X BT	ped: manner following: 534 BT	S.C. T145N R29W \$\frac{1}{4}\$ S34 \$1969 R.L.S. No. 6807
from which row N. Pine N. Pine Elm 8 in Steel si	eference or witne 22 inch N46°W 19 inch N1°E ch S37°E 8.6	ess monument 1 65.20 feet 45.90 feet 0 feet scri	rass tablet stamped are located in the et scribed SC $\frac{1}{4}$ Scaribed SC $\frac{1}{4}$ Scaribed X BT due east 2.70 feet	ped: manner following: 534 BT 34 BT	S.C. T145N R29W \$\frac{1}{4}\$ S34 \$1969 R.L.S. No. 6807
from which row N. Pine N. Pine Elm 8 in Steel si	eference or witne 22 inch N46°W 19 inch N1°E ch S37°E 8.6 gn post 72 in rence bearing	ess monument 65.20 feet 45.90 feet 60 feet scri ches long des	rass tablet stampers are located in the set scribed SC $\frac{1}{4}$ Scatter and SC $\frac{1}{4}$ Scatter are located in the set scribed SC $\frac{1}{4}$ Scatter are located in the scatte	ped: manner following: 534 BT 34 BT	S.C. T145N R29W \$\frac{1}{4}\$ S34 \$1969 R.L.S. No. 6807 sign 54-4 attached

this. GORDON E. CLOSE Public Notary Public, Cass County Mann. My commission expires July 28, 1971 Register of Deeds ..Deputy



