CERTIFICATE OF LOCATION OF GOVERNMENT CORNER  East Quarter		
10" BIRCH N&D E SIDE  14" BURR OAK N&D S SIDE  14" BURR OAK N&D W SIDE  "SKETCH OF REFERENCE TIES" (not to scale – bearings are magnetic) Ties are measured to center of monument unless otherwise noted.  UNITS = Metric Menglish  1 hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.	OF GOVERNMENT CORNER	A000597185  OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON 10/10/2013 11:50:59 AM AS DOC #: A000597185 PAGES: 2 REC FEES: 0.00 KATHRYN M. NORBY CASS COUNTY RECORDER
10" BIRCH N&D E SIDE  14" BURR OAK N&D S SIDE  14" BURR OAK N&D W SIDE  "SKETCH OF REFERENCE TIES" (not to scale – bearings are magnetic) Ties are measured to center of monument unless otherwise noted.  UNITS = Metric Menglish  1 hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.	Con "Chalance A of Cidence" for faither datable for health	(constant for consisting data)
(not to scale — bearings are magnetic)  Northing: 328844.221  Easting: 498779.034  NAD 83/2007 Adjustment.  Obtained by RTK GPS observations.  I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.	9 10  E SIDE  WOODS  14" BURR OAK N&D S SIDE  10" BURR OAK N&	
I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.	(not to scale — bearings are magnetic)  -N- Ties are measured to center of monument unless otherwise noted.	Northing: 328844.221 Easting: 498779.034  NAD 83/2007 Adjustment.
I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.	UNITS = □Metric ⊠English	Obtained by RTK GPS observations.
signature date	I am a duly Licensed Land Surveyor under the laws	of the State of Minnesota. $\frac{2 - / - / - }{}$

signature Jarrett M. Leas, Minnesota License No. 42619



Page 2 of 2 A000597185

## Statement of Evidence

East Quarter corner of Section 9, Township 138 North, Range 30 West, 5th Principal Meridian.

Aug. G.B.Wright, GLO Deputy Surveyor, in the notes of the subdivision of Township 138 North, Range 30 West set a post for the original corner and referenced it as follows:

18" N. Pine West 70 links (46.20 feet) 20" N. Pine N 55° E 46 links (30.36 feet) Said records are on file at the Minnesota Historical Society, St. Paul, Minnesota, copies are filed with the Cass County Surveyor's Office (CCSO).

June J.W.Curo, RLS 1428, County Surveyor, working for Pine River Township, Curo Field Book 2, page 79, on file in the CCSO, indicates setting an IM, "1/4 bet 9&10 flag and big mound".

Dec. B.Hippen, CCSO technician, records of the CCSO, found a 2 inch outside diameter iron pipe, flush, 20

2004 feet, more or less, west of fence corner, and witnessed as follows:

8" Birch N 30° W 17.27 feet 6" Burr Oak S 20° W 24.53 feet

10" Burr Oak S 74° W 21.85 feet

Nov. A KLJ survey crew found a 2" Iron Pipe, flush with ground, and is witnessed with the ties shown on the

2012 front of this certificate. Jarrett Leas, RLS #42619, after analysis of record and survey information accepts

this monument as the correct perpetuation of the corner.