

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter Corner of Section 31
Township 145 N, Range 26 W, 5th P.M.
STATE OF MINNESOTA, COUNTY OF CASS



A000599556

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

1/9/2014 1:30:06 PM

AS DOC #: A000599556

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR Dep

On _____, found a(n): _____
DATE

- left monument as found
- lowered monument
- removed monument (explain)
- raised monument

On 6/28/2012, set a(n): 5/8"x 48" Rebar With Aluminum
DATE
Cap 0.5' Up With Fence Post On North Side

See "Statement of Evidence" for further details (on back)

(reserved for recording data)

9" Aspen With Nail
And Disk 1' Up On
Northeast Side Double
Blazed With Tag



N 36° W
35.92'

10" Aspen With Nail
And Disk 1' Up On
Double Blazed Tree



N 59° E
21.30'

12" Aspen With Nail
And Disk 1' Up On
Double Blazed Tree





S 50° W
26.70'



32" White Oak With Nail
And Disk 1' Up On
North Side With Tag

S 77° E
9.24'

5/8"x 48" Rebar With
Aluminum Cap 0.5' Up With
Fence Post On North Side



"SKETCH OF REFERENCE TIES" (not to scale - bearings are magnetic)

Ties are measured to center of monument unless otherwise noted.

UNITS = Metric English

UTM COORDINATES, ZONE 15

Northing: 17200153.44

Easting: 1389943.07

NAD 83/1996 Adjustment.

Obtained by RTK GPS observations.

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision, and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Ross Wamre
signature

6/6/13
date

Ross Wamre, Minnesota License No. 45334

Page 1 of 2 A000599556



STATEMENT OF EVIDENCE: Corner common to Sections 31 and 32 of Township 145 North, Range 26
West of the 5th Principle Meridian.

1876; Benjamin C. Baldwin, for the Government Land Office established this corner and set a wooden post and witnessed by:

Tamarack 10" North 05° East, 50 Links

Tamarack 8" North 13° West, 55 Links

1926; State of Minnesota Department of Transportation Right-of-Way Plat No. 30-60A shows a ties from the East Corner of Section 31; 1281.8' South to the Centerline of Road. Information on file with the Minnesota Department of Transportation.

2010; Kadrmass, Lee & Jackson crew found no evidence of corner location or its accessories.

2012; Ross Wamre, RLS #45334, after analysis of record and survey information set a 5/8" x 8' rebar with an Aluminum Cap 0.5' up from ground according to MN Dot Right-of Way Plat 31-7 using recovered stationing and alignment course and distance. Witnesses established as shown on the face of this certificate.

Contacts pertaining to this corner are as follows:

Cass County Recorder's Office

Cass County Engineers Office

Cass County Surveyors Office

Northern Engineering and Consulting Inc.

United States Forest Service

MnDOT – District Office 2

Bureau of Indians Affairs – Bemidji

Bureau of Land Management's (BLM) Northeastern States Field Office