



A000600663

OFFICE OF THE COUNTY RECORDER
CASS COUNTY, MINNESOTA
CERTIFIED, FILED, AND/OR
RECORDED ON

2/27/2014 11:25:22 AM

AS DOC #: A000600663

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY
CASS COUNTY RECORDER

BY SR _____ Dep

Page 1 of 2
A000600663

Twp 136 Rge 30 Index No. G.0-21.0

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter corner of Section 11, Township 136 N., Range 30 W., 5th P.M.
State of Minnesota, County of Cass

At the corner location shown on the sketch:

On 1 June 2012 found _____ a 2 inch outside diameter iron pipe, up 0.9 foot,
_____ on North side of a Rail Road tie fence post for East to West fence line.

left monument as found lowered monument removed monument (explain)

On _____ placed _____

SKETCH OF REFERENCE TIES

NOT TO SCALE



Logged

16d duplex nail
up 1.0 feet in E side
of 11 inch Red Pine

16d duplex nail
up 1.0 feet in S side
of 6 inch Red Oak

SECTION 11

SECTION 12

Fence

Pasture

Field

16d duplex nail
up 1.0 feet in W side
of 10 inch Jack Pine

9'±

Fence

NOTE:

All bearings are true

Statement of evidence relative to this corner location is on the back of this page.

I hereby certify that this survey, plan or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the State of Minnesota.

Terry L. Freeman, Cass County Surveyor

Date 2/26/14 MN License No. 21367

**Index No. 13630G.0-21.0**Statement of Evidence**East Quarter corner of Section 11, Township 136 North, Range 30 West, 5th Principal Meridian.**

Aug. 1870 R.Cronk, General Land Office (GLO) Deputy Surveyor set a post for the original corner in his subdivision of this township and referenced it as follows:

8" J. Pine S 25° W 9 links (5.94 feet) 7" J. Pine N 39° E 18 links (11.88 feet)

The above record is on file with the Minnesota Historical Society in St. Paul, Minnesota, copies are filed with the Cass County Highway Department, Surveyor's Office (CCHD/SO).

March 1917 E.B. Horst, LS 376, Deputy County Surveyor, Survey Record Number 337, Book B, page 504, Curo Book 62, page 49, 54 and 78, on file in the CCHD/SO, states "at 2636.7 ft N intersect old post set for ¼ cor between secs 11 & 12 T136 R30 from which Old U.S. B.T. Jack Pine 8 sets S 25° W 9 lks (5.94 ft) plainly marked being a snag 5 ft high. Jack Pine 7 N 39° E 18 lks (11.88 ft) is gone." On page 78 he indicates a 2x48 inch I.M. was set for the corner.

May 2012 B.Hippen, CCHD/SO technician, records of the CCSO, found a 2 inch outside diameter iron pipe, up 0.9 foot, on the north side of a rail road tie fence post and witnessed as follows:

11" N. Pine N 06° W 76.81 feet 6" R. Oak N 74° E 41.68 feet
10" J. Pine S 28° W 68.39 feet

The monument, recovered and established references for the position are shown on the face of this document.

Analysis of the recovered record data, field evidence and survey measurements, indicates that the monument recovered by CCHD/SO in 2012 is the correct perpetuation of this corner.

County Coordinates (Cass County South)

Northing 265114.85

Easting 513086.97