

A000609636

OFFICE OF THE COUNTY RECORDER CASS COUNTY, MINNESOTA CERTIFIED, FILED, AND/OR RECORDED ON

2/18/2015 10:17:37 AM AS DOC #: A000609636 PAGES: 2 REC FEES: 0.00

KATHRYN M. NORBY CASS COUNTY RECORDER BY SR Dep TX#: 121093

Twp 135 Rge 30 Index No. E.0-05.0 CERTIFICATE OF LOCATION OF GOVERNMENT CORNER 7____,Township <u>135 N.</u> ,Range 30 W., 5th P.M. Northeast Corner of Section _ State of Minnesota, County of Cass At the corner location shown on the sketch: On Dec.15, 2014 found1/2" Capped iron pipe with RLS 43932 .05 feet above ground □ left monument as found ☐ lowered monument ☐ removed monument (explain) On placed SKETCH OF REFERENCE TIES 24" Twin Maple NOT TO SCALE Set Nail NE 6" Maple Set Näil SW KLS 43932 Up 0.05ft NOTE: All bearings are true. Coordinates are Maple Cass CO. South NAD 83 96 ADJ N=235752.765 Set Nail SF E=492436.692 Statement of evidence relative to this corner location is on the back of this page. I hereby certify that this survey, plan or

report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws

Daniel W. Skinner, Land Surveyor

MN License No. 40827

of the State of Minnesota.

Date 2-1-15



Page 2 of 2 A000609636

Index No. E.0-05.0

Statement of Evidence

Northeast Corner Section 7, Township 135 North, Range 30 West

Original US General Land Office Survey by T.B.Walker, set a wood post and bearing trees as noted:

15"	Aspen	S 25° W	5 links
7"	Aspen	N 20° E	24 links
16"	Sugar Maple	N 80° W	25 links
7"	Birch	S 40° E	40 links

Information on file with the Minnesota Historical Society in St. Paul, MN and copies are filed with the CCHD/SO.

- 1923 Curo Book 94, P. 148 shows that John Green found a stake for corner. Information on file with CCHD/SO.
- 2014 Karvakko Engineering found a ½in iron pipe with RLS 43932 .5ft above ground surface and accepted it as the corner.

Set Reference ties:

24"	Twin Maple	N 38°W	69.52 feet
6"	Maple	N 42° E	6.65 feet
20"	Maple	S 36° W	63.06 feet