



**A000670620**

**OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON**

**3/26/2021 8:15:48 AM**

**AS DOC #: A000670620**

**PAGES: 2**

**REC FEES: 0.00**

**KATHRYN M. NORBY  
CASS COUNTY RECORDER**

**BY NG Dep TX#: 170225**

I HEREBY CERTIFY THAT THIS DOCUMENT AND THE DATA CONTAINED HEREIN WAS PREPARED BY ME OR UNDER MY DIRECT SUPERVISION.

Mary T. Carlson 2/25/2021  
MARY T. CARLSON DATE

LICENSE NO. 40991

LAND SURVEYOR       PROFESSIONAL ENGINEER  
 COUNTY SURVEYOR       COUNTY ENGINEER

NAD 1983 (1996 HARN) CASS COUNTY NORTH ZONE COORDINATES  
N= 327504.216 E= 456063.902 US SURVEY FT  
(COORDINATES ARE SHOWN AS INFORMATION ONLY, SUBJECT TO VERIFICATION)

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

INDEX NO. V.3-5.0, MEANDER CORNER OF SECTIONS 31&32, TOWNSHIP 146, RANGE 29, 5TH P.M.  
STATE OF MINNESOTA, COUNTY OF CASS

AT THE CORNER LOCATION SHOWN ON THE SKETCH:

ON 7/09/2020 FOUND A(N) STAMPED BRASS CAP ATTACHED TO A 1" BY 36" IRON PIPE.  
 LEFT MONUMENT AS FOUND,       LOWERED MONUMENT,       REMOVED MONUMENT (EXPLAIN)  
 ON \_\_\_\_\_ DATE PLACED A(N) \_\_\_\_\_

## SKETCH OF REFERENCE TIES

DECLINATION 0°  
SKETCH NOT TO SCALE



MONUMENT MARKED:



To a 60d spike and washer in the base of a 15½" Jack Pine.



11.35'  
West



3.56'  
S45°W

±5'

MISSISSIPPI RIVER

T146-R29-S31

To a 60d spike and washer in the base of a 15½" Jack Pine.

T146-R29-S32

STATEMENT OF EVIDENCE RELATIVE TO THIS CORNER LOCATION IS ON BACK OF PAGE

Page 1 of 2  
A000670620



**STATEMENT OF EVIDENCE:** Meander Corner of Sections 31 and 32, South shore of the Mississippi River, Township 146 North, Range 29 West, of the 5th Principal Meridian.

1873; This corner was originally established by P.H. Conger, Deputy Surveyor under contract to the General Land Office (GLO), now the Bureau of Land Management (BLM). A copy of the plat of this township and hand copied field notes are available on the BLM website. These Field notes indicate a wood post was set to mark this corner position, which was witnessed by:

Norway Pine,	20",	North,	21 links,	13.86 feet;
Norway Pine,	12",	North 64° East,	29 links,	19.14 feet:

1934; (June) A Dependent Resurvey of T146N-R29W was performed by Cadastral Surveyor Hal D. Craig of the BLM. Mr. Craig affixed a stamped brass cap to a 36" by 1" iron pipe from the remains of the GLO witness trees described as follows:

Norway Pine stump,	22",	North,	21 links,	13.86 feet;
Norway Pine stump,	15",	North 64° East,	29 links,	19.14 feet:

He added the following witnesses:

Jack Pine,	7",	South 43° East,	131 links,	86.46 feet;
Jack Pine,	12",	South 15½° West,	150 links,	99.00 feet:

1968; (November) L. Elliott, C. Krause and L Bergeron, survey technicians for the United States Forest Service (USFS) recovered the 1934 monument and both witnesses, noting that the tree to the southwest was a 3' high stub. This information is found in Township Corner Restoration Book 2C, page 54. Bill Okerman, LS 6807, recorded an Affidavit as to Location of Government Corner as Document No. 275088. The following witnesses were added:

Jack Pine,	9",	South 56° East,	39.13 feet;
White Oak,	7",	South 47° West,	17.75 feet;
Jack Pine,	6",	South 50° West,	3.5 feet:

2020; (July) Itasca County Department of Surveying and Mapping personnel G. Robertson and T. Lasecki recovered the 1934 monument. No other evidence was readily recovered due to very thick foliage. Geodetic coordinates were established on the monument using a Fast Static observation. This information is found in the Itasca County 146-29 Field Book 2, page 25. The established witnesses are as shown on the face of this certificate.

***The chain of history indicates that this position is a direct perpetuation of the corner as established in 1875.***