



A000687370

OFFICE OF THE COUNTY RECORDER  
CASS COUNTY, MINNESOTA  
CERTIFIED, FILED, AND/OR  
RECORDED ON

8/25/2022 11:01:43 AM

AS DOC #: A000687370

PAGES: 2

REC FEES: 0.00

KATHRYN M. NORBY  
CASS COUNTY RECORDER

BY SF Dep TX#: 183873

I hereby certify that this survey, plan, or report was prepared by me or under my direct supervision and that I am a duly Licensed Land Surveyor under the laws of the state of Minnesota.

*Daniel J. McAninch* 25 August 2022

Daniel J. McAninch Date  
MN LIC. #25684

Page 1 of 2 A000687370

### CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North 1/4 Corner of Section 18, Township 136 N, Range 30, W P.M. 5th  
County of Cass, State of Minnesota

At the corner location shown on the sketch:

- On \_\_\_\_\_ found \_\_\_\_\_
- left monument as found     lowered monument     removed monument (explain)
- On January 12 2021 set 1 1/2" dia. aluminum pipe with a 1-1/2" magnetized cap

### SKETCH OF REFERENCE TIES

(NOT TO SCALE)



NAIL & WASHER  
S FACE 18"-12" DBL RED OAK

NAIL & WASHER  
WEST BASE 4" DIA FENCE POST

WOODED

BRUSH/PASTURE

S07-T136N-R30W

S18-T136N-R30W

WOODED

PASTURE


N45dW  
15.56

N05dE  
19.95

S35dW  
12.10

1-1/2"

NAIL & WASHER  
W BASE 13" MAPLE



Cap Stamping Detail

Cass County Coordinates  
(South Zone, 2011 Adj.)  
N: 259,548.400  
E: 492,138.304

**STATEMENT OF EVIDENCE:****NORTH QUARTER CORNER OF SECTION 18,  
TOWNSHIP 136 NORTH, RANGE 30 WEST,  
MAPLE TWP., CASS COUNTY, MINNESOTA**

**1870** The original public land survey was completed and a wood post was set to mark the corner. The bearing ties were marked and measured to.

8" White Birch	S30dW	13 links (8.6')
7" Aspen	N27dE	7 links (4.6')

**1893** A road survey map prepared by James Garfield indicates the easterly line of Section 18 was surveyed for the route. The map shows a 35 minute deflection at the East Quarter Corner of Section 18.

**2022** During a boundary survey, a Cass County survey crew conducted a thorough search in the vicinity of this corner. The corner of existing barbed wire fences running easterly and southerly was determined to be the best available evidence of the corner position. A 1" diameter aluminum monument with a 1-1/2" diameter cap was set and ties taken. See page 1 for corner ties. (County Project 2021-002) (Cass County Survey #9681)

**CASS COUNTY COORDINATES (NAD 83 2011 ADJUSTMENT)****N-262,253.050****E-489,446.645**

General Land Office Information on file in the MN historical Society, St. Paul MN. Copies on file in the Cass County Highway Department/Surveyors Office (CCHD/SO).

For additional information contact:  
**Cass County Highway Department**  
**County Surveyor's Office**  
8045 County Road 12  
Walker, MN 56484  
218-547-1211