


Index No. E 5

CASS COUNTY LAND CORNER RECORD

T. 133 R. 29 M. 5TH Coordinates: X _____ Y _____
NE 7 Corner common to sections 5, 6, 7, 8



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees
Species R. OAK W. OAK
Diameter 6" 10"
Bearing S 67W N 70W
Distance 415 LKS 322 LKS

Original Bearing Trees Found
Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed 1911 By JOHN CURD
Location filed COUNTY SURVEY RECORD BOOK "A" P. 424-443
Monument FIND OLD GOVT. B.T.: 10" W. OAK N 70W 312.5'
FIND REST. OF S.W. B.T. SET 4" X 36" IRON.
MONUMENT IN CONCRETE

Evidence of Subsequent Corner Restoration

Year of search 1911 By A. W. Moulster
Microfilm - Roll 105 BK 49 P. 44
FAD corner set by CURD

Bearing Trees, Reference Objects

Species BR. OAK BR. OAK
Diameter 5" 2 1/2"
Bearing N 57-25W N 76-20E
Distance 36.20' 32.97'

Bearing Trees, Reference Objects

ES

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search 1999 By CCSO
Find. impl. mag. PK & CO. RD. 18 flush
w/ bit. fe runs East.
TIES: P. Pole S 89° W 53.56'
(w. side, bottom) S. Post N 23° E 62.50'
12" W. Oak S 43° E 173.40'

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____