


T. 133 R. 30 M. 5TH Coordinates: X _____ Y _____
E 1/4 17 Corner common to sections 16 and 17



EXISTING SURVEYS

Original Government Survey

Year surveyed 1870
Original monument POST

Original Evidence Found

Year of search 1952 By _____
Monument found _____
63 1/2" NORTH OF E

Bearing Trees

Species	<u>WILLOW</u>	<u>BALM GILEAD</u>	
Diameter	<u>4"</u>	<u>6"</u>	
Bearing	<u>N 23 W</u>	<u>N 57 E</u>	
Distance	<u>14 LKS</u>	<u>123 LKS</u>	

Original Bearing Trees Found

Species	<u>SE GAR FRUIT</u>	<u>ELM</u>	<u>IRON PIN</u>
Diameter		<u>4"</u>	
Bearing	<u>NW</u>	<u>NE</u>	<u>ENE</u>
Distance	<u>98.53</u>	<u>99.6</u>	<u>90.0</u>

O = Corner

Subsequent Corner Restoration

Year surveyed 1911 By JOHN CURE
Location filed COUNTY SURVEY RECORD BOOK "A" P 357-360
Monument FOUND OLD CORN SLED SHOE AND ROOT
N.W. WILLOW BT. SET 2x48" GALVANIZED
I.P.
- also on microfilm - roll 115 6874 P. 49-50

Evidence of Subsequent Corner Restoration

Year of search 1984 By Comstock & DAVIS
Certificate Filed Doc. # 276577
Set Co. Cast iron

Bearing Trees, Reference Objects

Species	<u>1944</u>	<u>FOUND IRON PIN AT INTERSECTION</u>
Diameter	<u>OF ROADS</u>	
Bearing		
Distance		

Bearing Trees, Reference Objects

<u>Aspen</u>	<u>chisled "x" E.</u>	<u>chisled X</u>	<u>P.P.</u>
<u>8"</u>	<u>end 30" culvert</u>	<u>w. end 30" culvert</u>	
<u>NE</u>	<u>NE</u>	<u>NW</u>	<u>NW</u>
<u>103.45</u>	<u>18.11'</u>	<u>25.87</u>	<u>75.64'</u>

S.E. corner foundation NW 98.7

L-9

Subsequent Corner Restoration

Year surveyed 6/99 By MN/Dot
Location filed CCSO
Monument CIM from 1984 also culvert
and foundation witnesses, added:
P. Polc N 32°W 73.77' to S.R.P.

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Ron Murphy - Comstock & Davis 1984
Doc. # 276577
J. Kramer # 23668 July 2003
Cert. of Survey shows Mon. Found

Remonumentation certificate prepared #432820
Filed at CCSO & Recorder

By MN/Dot #23668
Date 2/8/01